

# FUZZYSCAN L780

## 1D Handheld Laser Imager



### A durable, high-performance laser imager for industrial and general applications

Powered by the FuzzyScan imaging platform, L780 delivers high-performance and exceptional speed. Its ergonomic design provides users with superior comfort, while the sharp laser beam allows for precise targeting. This rugged imager offers swift data captures on a wide array of 1D barcodes and stacked symbologies. The L780 is engineered to boost efficiency and convey outstanding value.

- Sharp laser beam for quick and precise targeting
- Supports PDF417 and Composite Codes
- Reads various challenging and problematic barcodes
- Reads electronic barcodes from smartphone screens
- Withstands drops from 2m to concrete
- Antimicrobial model available for healthcare applications
- Clear audio and visual feedback
- Optional vibrator for tactile confirmations
- Configuration can be done through iCode
- Advanced data formatting with DataWizard
- Inherits the powerful FuzzyScan DNA

### Scan All Your Needs

Powered by exclusive FuzzyScan Imaging technology, the L780 imager is capable of reading a vast array of challenging and problematic barcodes. The L780 imager is capable of scanning wrinkled, dirty, or soiled barcodes that are displayed on paper, plastic, metal, digital screens, and curved surfaces.

### Cutting Edge Imaging Technology

Powered by state-of-the-art AI-based machine vision, the exclusive FuzzyScan imaging technology is a performance-driven innovation. Incorporated with an advanced optical design and a powerful hardware platform, all Cino scanners deliver unrivaled scanning speed and accuracy across all types of real-world barcodes.

### Reads PDF417, GS1, and UDI Barcodes

The F680 series can capture regular barcodes from a long distance, as well as very high-density barcodes within an optimal depth of field. In addition to a vast array of linear barcodes, it supports linear-stacked, PDF417, composite, GS1, and UDI codes.

### Enhanced User Experiences

Designed with sharp aiming and multifaceted notification feedback via visual, audio, as well as tactile indications, the L780 delivers superior usability and a great user experience.

### Clear Audio and Visual Feedback

The L780 imager uses audio and visual indicators to indicate its various statuses. The Imager has a loud beeper with an adjustable volume and tone. The LED lights emit conspicuous and programmable multi-color signals to help users clearly identify the current status at a quick glance.



## FUZZYSCAN DNA

### Tactile Feedback Option

Beeping sounds are considered disruptive in certain circumstances. Vibration is available as an option on this imager to provide tactile feedback to users. This is suitable for both quiet and noisy environments.

### Built-in USB Port

With a built-in USB port, your scanner can operate with corded functionalities including corded transmissions, firmware upgrades, and scanner configuration for superb flexibility. Alternatively, it can be connected to a power source while working to further reduce downtimes and productivity losses.

## Value Beyond Measure

FuzzyScan DNA is a collection of unique features that come with every Cino imagers at no additional cost. It delivers exceptional value beyond barcode scanning. Aside from the exclusive FuzzyScan imaging technology, Cino's scanners provide the following distinctive features to elevate user's experience:

### DataWizard

DataWizard is a unique feature to perform advanced data formatting and complex data processing.

### iCode

The iCode feature is a macro command barcode that allows one-step configuration with a single scan.

### Multilingual Edge

Multilingual Edge is a useful feature that enables data output in your desired language.

### Smart Scene

Smart Scene offers a choice of several preset configurations for various application scenarios to achieve optimal scanning performance.

### Security Plus

Security Plus is a user-defined security mechanism that prevents the access of unauthorized barcode scanners.

### FuzzyScan Enabling Solution

FuzzyScan Enabling Solution is a suite of software utilities that enables easy integration, management, and deployment of scanners.

# SPECIFICATIONS

## Performance Characteristics

Optical System	High performance linear imaging engine
Print Contrast	20% minimum reflective difference
Light Source	630nm visible red LED with laser aiming
Minimum Resolution	3 mil (Code 39, PCS 0.9)
Reading Range *1	13 mil (0.33mm) UPC/EAN up to 24"
Scan Rate	Dynamic scanning rate up to 500 scans per second
Reading Direction	Bi-directional (forward and backward)
Pitch / Skew / Tilt	±65° / ± 65° / ± 55°
Configuration Setup	Command barcodes FuzzyScan iCode FuzzyScan PowerTool
Data Processing	DataWizard
User Interfaces	3 LEDs for power, good read and status indications Programmable beeper Optional vibration

## Electrical Characteristics

Operating Voltage	3 LEDs for power, good read and status indications Programmable beeper Optional vibration
Operating Current	Operating : Typical 190 mA @5VDC Standby : Typical 90 mA @5VDC

## Physical Characteristics

Dimensions	97.8 mm (L) x 70.5 mm (W) x 156.2 mm (D) 3.85 in. (L) x 2.77 in. (W) x 6.15 in. (D)
Weight	157g (cable excluded)
Color	Classic Black, Ivory White
Host Interfaces	USB HID (USB Keyboard) USB VCOM (USB COM port emulation) USB OEM POS Standard RS232

1. The Reading Range are measured under Cino's test environmental condition.
2. Codablock F, Code 16K, and Code 49 are available upon request.

## Supported Symbolologies

1D Linear Codes	Code 39, Code 39 Full ASCII, Code 32, Code 128, GS1-128, Codabar, Code 11, Code 93, GS1 DataBar, Standard & Industrial 2 of 5, Interleaved & Matrix 2 of 5, IATA, UPC/EAN/JAN, UPC/EAN/JAN with Addendum, Telepen, MSI/Plessey & UK/Plessey
Linear-stacked *2	PDF417, Micro PDF417, Composite Codes, Codablock F, Code 16K, Code 49, Linear-stacked
Postal Barcodes	German Post, Korean Post, China Post

## User Environment

Drop Specifications	Withstands multiple drops from 2.0m (6.6ft) to concrete
Environmental Sealing	IP52
Operating Temperature	-10 °C to 50 °C (14 °F to 122 °F)
Storage Temperature	-40 °C to 70 °C (-40 °F to 158 °F)
Humidity	0% to 95% relative humidity, non-condensing
Ambient Light Immunity	0 ~ 100,000 Lux
ESD Protection	Functional after 15KV discharge

## Safety & Regulatory

EMC	CE, UKCA, FCC, BSMI, RCM, KC, VCCI
Safety	LED Eye Safety IEC62471, Exempt Group Laser Eye Safety IEC60825-1, Class 1
Environmental	Compliant with RoHS and REACH

## Accessories

<b>Cables</b>	RS232 Serial Cable USB-A Cable USB-C Cable USB Power Cable
<b>Others</b>	US100 SmartStand Universal Holder Power Supply Unit (5VDC, 2A outlet)

