



FUZZYSCAN

Barcode Programming Manual

International Edition, A17 Release



Revision History

REV.	Date	Briefing	
A1	Sep, 2022	[New]	First release
A2	Nov, 2022	[New]	Added User-defined Function Key
		[New]	Added Appendix - Function Key Character Table
		[New]	Added OK/NG indicator-related options of OK/NG Signal Output
		[New]	Added GS1 Prefix/Suffix Output
		[New]	Added GS1 Format Mismatch Rule
		[Changed]	Changed default option of OK/NG Beeping
		[Changed]	Renamed to Handheld Decode Timeout and Handsfree Decode Timeout
		[Changed]	Renamed to Handheld Center Alignment and Handsfree Center Alignment
		[Changed]	Renamed to 2D Handheld Illumination & Aiming Control and 2D Handsfree Illumination & Aiming Control
		[Changed]	Changed option code of Fixed Mount Scanners Operation Mode
A3	Jan, 2023	[New]	Renamed Presentation Trigger to Presentation Trigger Select
		[New]	Renamed Presentation Scan to Presentation Continuous Scan
		[New]	Changed default option of MicroPDF Readability
A4	Mar, 2023	[Changed]	Changed applied model of USB Data Merge to all models
A5	May, 2023	[New]	Added Keyboard Num Lock Auto Detect
		[New]	Added 2D Presentation Background Lighting
		[Changed]	Changed default value of Auto-sense Control of Bluetooth scanners
A6	Jul, 2023	[New]	Added GS1 DataBar Limited Security Level
		[New]	Added Companion Function Key 1 and Function Key 2 Control
A7	Sep, 2023	[New]	Added I/O Active State
		[Changed]	Renamed Power-on Indicator to Power Indicator
A8	Oct, 2023	[New]	Added Modifier Key Output Control
		[Changed]	Revised 2D Smart Scene
A9	Dec, 2023	[New]	Added IR sensitivity
		[New]	Added Alt Code Digit Control
		[New]	Added Alt Code BREAK Control
		[New]	Added IR Sensitivity
		[New]	Added options of Arabic, Thai, Russian, and Vietnamese layouts to Keyboard Country Layout
		[New]	Added option of 230.4K BPS to Serial Baud Rate
		[New]	Added option of Image Motion Detect to Presentation Trigger Select
		[New]	Added functions of QR Append, QR Inverse, and QR Mirror Image to Micro QR code
		[New]	Added supported category Fixed Mount Scanners to Presentation Trigger Select
		[New]	Added option of Polish to Keyboard Country Layout
		[Changed]	Renamed UPC Leading Digit 1 to UPC E1 Readability
A9	Dec, 2023	[Changed]	Changed default option of Presentation Continuous Scan
		[Changed]	Renamed Composite Code to GS1 Composite Code

Revision History (continued)

REV.	Date	Briefing	
A10	Feb, 2024	[Changed]	Changed default value of 2D scan engine to Regular Aiming under 2D Aiming Select
A11	Apr, 2024	[Changed]	Renamed 1D Reading Redundancy to Reading Redundancy
A12	Aug, 2024	[Changed]	Changed 1D scanner support for 1200 BPS in Serial Baud Rate
A13	Sep, 2024	[New]	Added Illumination Color, DPM Illumination, DPM Diffused Illumination, Illumination Rotation Interval, DPM Mode, 2D Illumination Intensity, Low Power State and Time Delay to Low Power State
		[New]	Added option of user-defined decoding area to Handheld/Hands-free Alignment
A14	Sep, 2024	[Changed]	Revised Handheld/Hands-free Alignment
A15	Dec, 2024	[New]	Added USB Legacy Mode, Trigger Toggle, Trigger Number, ROI, Swift Serial Reading, User-defined Serial Trigger On/Off, Command Barcode Lock
A16	Aug,2025	[New]	Added Reread Delay Verification, OCR Readability, OCR Inverse Reading, OCR Reading Orientation, OCR Predefined Template, OCR Reading Redundancy, Voice Feedback, Voice Feedback Delay, Reset Reread Delay, Batch Reading
		[Changed]	Changed Presentation Continuous Scan options
A17	Mar,2026	[New]	Added Auxiliary Illumination, Intelli Button Select, Barcode Position

Disclaimer

Cino makes no warranty of any kind regarding this publication, including, but not limited to, the implied warranties of merchantability and fitness for any particular purpose. Cino shall not be liable for any technical or editorial errors or omissions contained herein, nor for incidental or consequential damages resulting from the furnishing, performance, or use of this material. Cino disclaims all responsibility for the selection and use of software and/or hardware to achieve intended results. Cino reserves the right to make changes to specifications and other information contained in this document without prior notice, and the reader should, in all cases, consult Cino to determine whether any such changes have been made. The information in this publication does not constitute a commitment on the part of Cino.

Copyright

This document contains proprietary information protected by copyright. All rights are reserved. No part of this document may be photocopied, reproduced, or translated into any language in any form without the prior written consent of Cino. This restriction includes electronic or mechanical means, such as photocopying, recording, or the use of information storage and retrieval systems.

© COPYRIGHT CINO GROUP • PC WORTH INT'L CO., LTD. ALL RIGHTS RESERVED.

About This Manual

This programming manual provides general instructions on setting up Cino's FuzzyScan scanners.

Chapter 1, [Overview](#)

This chapter provides an overview of system commands, quick set commands, family codes, and option codes used when setting up FuzzyScan barcode scanners. It also presents general information on Cino's programming procedures and includes simple flowcharts to help users better understand the configuration process.

Chapter 2, [Interface Settings](#)

This chapter presents parameters to assist users with host interface selection and related configurations. It covers settings for keyboard interface output (such as keypad layout and code pages) and serial interface output (such as baud rate, data frame, and more).

Chapter 3, [Barcode Reading](#)

This chapter contains parameters that help users configure their scanners to read different types of barcodes supported by FuzzyScan scanners. Detailed settings for each code type are also included. Users can enable the Barcode ID function to identify the type of code being scanned.

Chapter 4, [Operation Modes](#)

This chapter provides a complete list of available operation modes for each product series. To fulfill the needs of different application scenarios, the scanners' default modes and available mode options vary from series to series.

Chapter 5, [Operation Control](#)

This chapter presents parameters related to the scanner operation. It includes settings for general scanner functions, user feedback control (such as buzzer and vibration), and special parameters specific to different scanners.

Chapter 6, [Bluetooth Settings](#)

The chapter covers Bluetooth-related settings of FuzzyScan cordless scanners. The parameters discussed are specific to Bluetooth models (such as batch scanning and validation scanning) and include general Bluetooth settings such as device name, security, radio link and time-out settings.

Chapter 7, [Data Modifications](#)

This chapter presents parameters for modifying data before it is transmitted by the scanner. Users can add extra characters, include informative elements, and control the GS1 parsing tool.

Chapter 8, [Appendix](#)

The Appendix contains additional information essential for programming FuzzyScan barcode scanners. It includes tables for 1D barcode ID, 2D barcode ID, keyboard function codes, ASCII/HEX conversion, and code pages. This section also covers quick set commands, systems commands, and option codes.

Other Documentation

You may also refer to the documents below for additional information.

FuzzyScan Quick Start Guide

Quick introduction to scanner setup and operation

FuzzyScan User Manual

Information pertaining to the setup and operation of Cino barcode scanners

FuzzyScan Serial Command Manual

Information on using serial commands to program Cino barcode scanners

Table of Contents

Revision History.....	1
Disclaimer	3
Copyright	3
About This Manual.....	4
Other Documentation	5
Table of Contents.....	6
1 COMMAND OVERVIEW.....	13
1.1 Introduction	14
System Commands.....	14
Family Codes	14
Option Codes.....	14
Quick Set Commands	14
1.2 Programming Procedures	15
1.3 Notational Conventions.....	16
1.4 Programming Flowcharts.....	17
Program & End.....	18
Single Scan Selection.....	19
Multiple Scans Selection	20
Cycling Scan Selection	21
Dual Level Selection	22
System & Quick Set Commands	23
2 INTERFACE SETTINGS.....	25
2.1 Host Interface Settings.....	26
Host Interface Selection	27
2.2 Keyboard Interface Settings	28
Caps Lock.....	29
Caps Lock Release.....	30
Num Lock Auto Detect	31
Keyboard Record Suffix.....	32
Key Pad Emulation	33
Upper/Lower Case.....	34
Keyboard Intercharacter Delay	35
Keyboard Intermesssage Delay	36
Keyboard Interfunction Delay	37
Keyboard Country Layout.....	38
Keyboard Encoding Country Code Page	39
Keyboard Output Country Code Page.....	40
Alt Code Digit Control	41
Alt Code Break Control.....	42

User-defined Function Key	43
USB Data Merge	44
USB Legacy mode	45
Modifier Key Output Control.....	46
2.3 Serial Interface Settings.....	47
STX/ETX Transmit	48
Serial Record Suffix.....	49
Serial Intermessage Delay.....	50
Serial Intercharacter Delay	51
Serial Interfunction Delay	52
Handshaking Protocol	53
Response/Baud Rate/Data Frame	54
Serial Encoding Country Code Page.....	55
Serial Output Country Code Page	56
Serial NAK Retry Count	57
ACK Indication	58
3 BARCODE READING.....	60
3.1 Code ID	61
Code ID Transmit.....	62
Code ID – 1 Character	63
3.2 Barcode Readability.....	65
Readable Barcode Settings	66
3.3 Barcode Settings	68
Code 39/32, Trioptic Code 39.....	69
Code 39.....	70
Code 93.....	73
Code 128	74
Codabar.....	76
UPC.....	79
EAN.....	83
EAN – Prefix	87
UCC Coupon Extended Code	89
IATA.....	90
Interleaved 25 (ITF).....	92
Code 25 Family	93
Code 11.....	95
MSI	96
UK/Plessey.....	98
Telepen	100
PDF417/MicroPDF417	102
QR Code/Micro QR Code.....	103

Data Matrix	106
MaxiCode	108
Aztec Code	109
Australia Post Code.....	111
British Post Code.....	112
Netherlands KIX/Posi LAPA Code.....	113
Japan Post/Korea Post Code	114
US Planet	115
US POSTNET	116
Intelligent Mail	117
GS1 128.....	118
GS1 DataBar.....	119
GS1 Composite Code.....	121
OCR A and OCR B	122
4 OPERATION MODES	124
4.1 Operation Mode Settings.....	125
Operation Mode – Corded Imager.....	126
Operation Mode – Cordless Imager	127
Operation Mode – On Counter Scanner.....	128
Operation Mode – Companion Scanner	129
Operation Mode – Fixed Mount Scanner.....	130
Operation Mode – Scan Module	131
5 OPERATION CONTROL	132
5.1 Scanner Operation	133
Reread Delay/Good Read Delay	134
Reread Delay Verification.....	135
Reset Reread Delay	136
Voice Feedback Delay.....	137
Handheld Decode Timeout	138
Hands-free Decode Timeout	140
Presentation Scanning Activation.....	141
Presentation Continuous Scan	142
Object-in/Object-out Message Output	143
2D Image Sensitivity	144
IR Sensitivity	145
1D Barcode Inverse Reading	146
Hands-free Timeout	147
Auto-sense Control	148
Auto-sense Mode Select	149
Laser Auto-sense Power Off Timeout	150
NG Message Output	151

Handheld/Hands-free Alignment.....	152
ROI	155
Unique Barcode Reporting.....	157
2D Smart Scene.....	158
DPM Mode	159
Swift Serial Reading	160
Batch Reading.....	161
Low Power State.....	162
Time Delay to Low Power State	163
Reading Redundancy.....	164
1D Scan Rate.....	165
1D Reading Direction Indication	166
Forward/Backward-read Indication.....	167
OK/NG Signal Output.....	168
OK/NG Signal Active State.....	169
OK/NG Signal Duration.....	170
I/O Active State.....	171
User-defined Serial Trigger On/Off.....	172
Intelli Button Select	173
Barcode Position	174
Companion Function Key Control.....	175
Command Barcode Lock.....	176
5.2 Illumination Settings.....	177
2D Illumination & Aiming Control.....	178
2D Illumination Intensity	179
Auxiliary Illumination.....	180
2D Aiming Select/Pre-decode Aiming	181
2D Presentation Background Lighting.....	182
Laser Aiming Control	183
Laser Aiming Select, Pre-decode Aim	184
Illumination Color	185
DPM Illumination	186
DPM Diffused Illumination	187
Illumination Rotation Interval.....	188
5.3 Audio & Indicator Settings.....	189
Buzzer Tone/Buzzer Volume	190
Good Read Beeping	191
Voice Feedback	192
Power On/Off Beeping	193
Good Read Indicator, Power Indicator.....	194
Vibration Control.....	195

Good Read Duration.....	196
OK/NG Beeping	197
6 BLUETOOTH SETTINGS	199
6.1 General Bluetooth Settings	200
BT Device Name	201
BT PIN Code.....	202
BT Discoverable Protocol	203
BT Link Quality.....	204
BT Out-of-range Scanning.....	205
BT Radio Off Timeout.....	206
BT Power off Timeout.....	207
BT On-screen Keyboard.....	208
BT HID Transmit Delay	209
BT Connect Beeping Control & Select.....	210
BT Battery Low Beeping	211
BT Low Power Link Indicator.....	212
BT Sniff Control	213
BT Cradle PAIR Lock	214
6.2 Bluetooth Special Modes	215
Batch Scanning Link Control	216
Batch Scanning Data Transmit.....	217
Batch Scanning Data Delete.....	218
Batch Scanning ID Output.....	219
Batch Scanning Quantity Transmit	220
Batch Field Delimiter	221
Validation Scanning Link Control	222
Validation Scanning Master Data	223
Validation Scanning Output Select	224
Companion FN2 Select.....	225
7 DATA MODIFICATION	227
7.1 Global Settings	228
Preamble.....	229
Postamble	230
Dollar Sign Convert.....	231
FNC1 Transmit	232
Data Length Transmit.....	233
Code ID Transmit.....	234
ECI ID Transmit.....	235
7.2 GS1 Settings.....	236
GS1 Special Function.....	237
GS1 1st FNC1 Transmit	238

GS1 Noninitial FNC1 Transmit.....	239
GS1 AI Transmit	240
GS1 Failure Rule	241
GS1 Prefix/Suffix Output.....	242
GS1 Format Mismatch Rule.....	243
GS1 Date Field 'DD=00' Transmit	244
GS1 Decimal Point Insert	245
GS1 Element String Separator	246
GS1 Data Separator	247
8 APPENDIX	249
8.1 Code ID Table - 1D Barcodes	250
8.2 Code ID Table - 2D Barcodes	251
8.3 ASCII Input Shortcut	252
8.4 HEX/ASCII Reference Table	252
8.5 Function Key Output Table	253
8.6 Function Key Character Table	254
8.7 Table of Corresponding Languages.....	258
8.8 Unicode Hex Input Setup	259

1 Command Overview

This chapter contains an overview of the system commands, quick set commands, family codes, and option codes used when setting up FuzzyScan barcode scanners. It also presents general information on programming procedures, as well as simple flowcharts to help users better understand the configuration process.

1.1 Introduction

FuzzyScan command barcodes are specially designed barcodes that allow you to program Cino scanners. They can be grouped into three main categories: System Commands, Family Codes and Option Codes. Further details and programming flowcharts are provided below.

System Commands

System Commands direct FuzzyScan imagers to perform immediate operations, ie. enter programming mode (**PROGRAM**), exit programming mode (**END**), list system information (**SYSLIST**), and return to factory settings (**F_DEFAULT**). It will take a few seconds to complete the system command operations, so users must wait for the completion beeps before scanning another barcode.

Family Codes

Each parameter has a specific family code as its identifier. More than one hundred family codes available.

Option Codes

Option Codes are a set of command barcodes represented by the characters “0-9”, “A-F” and **FIN** (finish selection). For most settings, you must choose at least one option code after selecting a family code to set the desired parameter.

Quick Set Commands

Quick set commands are command barcodes designed to rapidly configure your FuzzyScan imager to a specific operation mode, host interface setting, Bluetooth link mode, or keyboard language layout.

1.2 Programming Procedures

Selected parameters are stored in the internal Flash Memory ASIC or non-volatile memory, and are retained even after the scanner is powered off.

Most family codes require the **Single Scan Selection** programming procedure. Other family codes use more sophisticated procedures, such as **Multiple Scans Selection**, **Cycling Scan Selection** or **Dual Level Selection**. The flowchart for each procedure is provided below.

Beeping indications for each FuzzyScan model can be found in the corresponding user manuals. These indications help users recognize the scanner's status during configuration.

1.3 Notational Conventions


Conventions	Descriptions	
◀	Factory Default Value	
PP	SS : Single scan selection MS : Multiple scans selection	CS : Cycling scan selection DS : Dual level scan selection
OC1	Option Code 1	
OC2	Option Code 2	
()	Necessary Option Code	
[]	Selectable Option Code	

Conventions	Descriptions	
ALL	Family Code applies to all FuzzyScan models	
2D ONLY	Family Code only applied to FuzzyScan 2D imager models: A800/BT, A700/BT, A600/BT, A500, FA500, FA400, PA600, S600, SE6000__series	
1D ONLY	Family Code only applied to FuzzyScan linear imager models: F800/BT, F700/BT, F600/BT, F500, L700/BT, L600/BT, FM400, PF600BT, PL600BT, SM400/300 series	
HANDHELD	Family Code only applied to FuzzyScan handheld models: A800/BT, A700/BT, A600/BT, A500, F800/BT, F700/BT, F600/BT, F500, L700/BT, L600/BT, PA600BT, PF600BT, PL600BT series	
COMPANION	Family Code only applied to FuzzyScan companion models: PA600BT, PF600BT, PL600BT series	
FIXED MOUNT	Family Code only applied to FuzzyScan fixed mount models: FA500, FM500, FA400, FM400 series	
SCAN ENGINE	Family Code only applied to FuzzyScan scan engine/module models: SE6000, SE400/300, SM6000, SM400/300 series	
SCAN MODULE	Family Code only applied to FuzzyScan integrated scan module models: IM600, IM300 series	
ON COUNTER	Family Code only applied to FuzzyScan on-counter models: S600 series, HS600 series	
CORDED	Family Code applies to FuzzyScan handheld corded models	
CORDLESS	Family Code applies to FuzzyScan handheld cordless models	
LASER ONLY	Family Code only applied to FuzzyScan laser imager models: L700/BT, L600/BT, PL600BT series	
BLUETOOTH	Family Code only applied to FuzzyScan Bluetooth models: A800BT, A700BT, A600BT, F800BT, F700BT, F600BT, L700BT, L600BT, PA600BT, PF600BT, PL600BT series	

1.4 Programming Flowcharts


This section provides a simplified overview of how to program your scanner. Each flowchart is organized to guide you through a specific scanning sequence.

Program & End




It will take 3-4 seconds for the parameters to be stored after scanning "END". Please **do not** turn off your scanner before hearing the completion beep. Otherwise, the settings may be lost.


Single Scan Selection




Multiple Scans Selection




Cycling Scan Selection



Dual Level Selection



System & Quick Set Commands



2 Interface Settings

This chapter presents different parameters to help users with host interface selection and related configurations. It covers settings for keyboard interface output (such as keypad layout and code pages), and serial interface output (such as baud rate, data frame, and more).

2.1 Host Interface Settings

This section provides the command barcode for configuring the host interface settings of your scanner. Scan the “**Host Interface**” command barcode to select the desired host interface for your scanner.


Host Interface Selection



Program

ALL

Family Code	PP	Parameter Selection	Option Code
 Host Interface	MS	[New] USB OEM	05
	MS	[New] RS232 Serial	06
	MS	[New] USB CDC/Virtual COM	09
	MS	[New] Laser Emulation (1D Handheld only)	17
	MS	[New] USB HID Keyboard ◀	18



2.2 Keyboard Interface Settings

This section provides a series of command barcodes for configuring the keyboard, alt code and modifier settings of the scanner. Users can find the functional details of each command barcode and specified parameter selection.

Caps Lock




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 Caps Lock	SS	Caps Lock Off ◀	0
	SS	Caps Lock On	1
	SS	Auto Detect	2

Caps Lock is designed to control whether the character outputs in uppercase or lowercase.

- **Caps Lock Off:** When selected, the scanner transmits data in its **original state** if the host keyboard’s “Caps Lock” is **off**, or in the **opposite state** if the host keyboard “Caps Lock” is **on**.
- **Caps Lock On:** When selected, the scanner transmits data in the **opposite state** if “Caps Lock” on host keyboard is **off**, or transmits data in the **original state** if “Caps Lock” on the host keyboard is **on**.
- **Auto Detect:** When selected, the scanner always transmits data in the **original state** with the help of special transmission handshaking with the host device.
- Only available with IBM PP/AT, PS/VP, PS/2 series personal computers and compatible machines.



Caps Lock Release



Program

ALL

Family Code	PP	Parameter Selection	Option Code
 Caps Lock Release	SS	Caps Lock On, Caps Off ◀	0
	SS	Caps Lock On, Shift Off	1

Caps Lock Release controls how to release “Caps Lock” on host keyboard, by pressing the “Caps Lock” key again or by pressing the “Shift” key instead.

OPTION CODE

 0	 4	 7	 9	 C
 1	 5	 8	 A	 D
 2	 6	<div style="border: 1px solid blue; padding: 5px; display: inline-block;">  FIN </div>	 B	 E
 3			 F	
 END			 FACTORY DEFAULT	

Num Lock Auto Detect




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 Num Lock Auto Detect	SS	Disable ◀	3
	SS	Enable	4

Num Lock Auto Detect: When enabled, the scanner can successfully send out characters using Alt codes regardless the state of the Num Lock.



Keyboard Record Suffix



Program

ALL


Family Code	PP	Parameter Selection	Option Code
 Keyboard Record Suffix	SS	None	0
	SS	RETURN ◀	1
	SS	TAB	2
	SS	SPACE	3
	DS	User-defined character (1 character)	5, (00-7F)

The table below shows the complete **Keyboard Interface Message String (USB HID)**:

Preamble	Scanned Data Length	Prefix Code ID	Scanned Data	Suffix Code ID	Postamble	Record Suffix (KB)
1-15 char.	2-4 digits	1 or 3 char.	Variable length	1 or 3 char.	1-15 char.	1 char.

To enter the character, refer to the **HEX to ASCII Conversion Table** below:

L \ H	0	1	2	3	4	5	6	7
0	NUL	DLE	SPACE	0	@	P	`	p
1	SOH	DC1	!	1	A	Q	a	q
2	STX	DC2	*	2	B	R	b	r
3	ETX	DC3	#	3	C	S	c	s
4	EOT	DC4	\$	4	D	T	d	t
5	ENQ	NAK	%	5	E	U	e	u
6	ACK	SYN	&	6	F	V	f	v
7	BEL	ETB	'	7	G	W	g	w
8	BS	CAN	(8	H	X	h	x
9	HT	EM)	9	I	Y	i	y
A	LF	SUB	*	:	J	Z	j	z
B	VT	ESC	+	;	K	[k	{
C	FF	FS	,	<	L	\	l	
D	CR	GS	-	=	M]	m	}
E	SO	RS	.	>	N	^	n	~
F	SI	US	/	?	O	_	o	DEL



Key Pad Emulation




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 Key Pad Emulation	SS	Disable ◀	0
	SS	Enable	1

Key Pad Emulation: When enabled, the scanner outputs numeric characters as keystrokes on the key pad when “Num Lock” is on. When disabled, it outputs numeric characters as keystrokes on the typewriter keys. This function is only available with IBM PP/AT, PS/VP, PS/2 series personal computers and compatible machines.



Upper/Lower Case



Program


ALL

Family Code	PP	Parameter Selection	Option Code
 Upper/Lower Case	SS	Normal case ◀	0
	SS	Inverse case	1
	SS	Upper case	2
	SS	Lower case	3

Upper/Lower Case controls whether the output character(s) are in upper or lower case when the scanner is in:

- **Normal case:** The scanner transmits every data character in its original font case.
- **Inverse case:** The scanner alters the font case of every data character from upper case to lower case or from lower case to upper case before transmitting it out.
- **Upper case:** The scanner transmits every data character in upper case regardless of its original font case.
- **Lower case:** The scanner transmits every data character in lower case regardless of its original font case.

Be aware that **Caps Lock** is still effective with Keyboard Upper/Lower Case function. In other word, if Caps Lock is ON on the host keyboard, the output font case should be inverted to the font case mentioned in the options above.



Keyboard Intercharacter Delay




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 Keyboard Intercharacter Delay	SS MS	None ◀ 1-99 (x5) ms	FIN (2 digits)

Keyboard Intercharacter Delay is the time delay between characters transmitted by the scanner. Use this parameter to synchronize data communication when:

- Data transmission speed is too fast, causing characters to be skipped;
- Multitasking operation system or host computers in a network may slow down keyboard handling;
- Various notebook or desktop PC systems require different timing configurations.
- Add one extra unit as safety margin when configuring this parameter.
- After scanning the 2 digits, the selection ends automatically.



Keyboard Intermessage Delay




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 Keyboard Intermessage Delay	SS	None ◀	FIN
	MS	1-99 (x5) ms (All corded series)	(2 digits)
	MS	1-99 (x10) ms (All Bluetooth series)	(2 digits)

- **Keyboard Intermessage Delay** is the time delay between messages transmitted by the scanner. Increasing this delay will help host applications process the incoming data on time.
- After scanning the 2 digits, the selection ends automatically.



Keyboard Interfunction Delay




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 Keyboard Interfunction Delay	SS MS	None ◀ 1-99 (x5) ms	FIN (2 digits)

- **Keyboard Interfunction Delay** is the time delay between two data segments divided by a function character.
- After scanning the 2 digits, the selection ends automatically.



Keyboard Country Layout




Program

ALL

Family Code	PP	Parameter Selection		Option Code	
 <p>Keyboard Country Layout</p>	SS	USA (QWERTY) ◀	Denmark (QWERTY)	00	12
	SS	France (AZERTY)	Belgium (AZERTY)	01	13
	SS	Germany (QWERTZ)	Swiss German (QWERTZ)	02	14
	SS	United Kingdom - UK (QWERTY)	Iceland (QWERTY)	03	15
	SS	Canadian French (QWERTY)	Japan (DOS/V)	04	16
	SS	Spain (Spanish, QWERTY)	Czech (QWERTY)	05	17
	SS	Sweden/Finland (QWERTY)	Arabic (101)	06	20
	SS	Portugal (QWERTY)	Thailand	07	23
	SS	Norway (QWERTY)	Russia (JCUKEN)	08	24
	SS	Spain (Latin America, QWERTY)	Vietnam (QWERTY)	09	26
	SS	Italy (QWERTY)	Polish	10	27
	SS	Netherlands (QWERTY)	Universal	11	99

Keyboard Country Layout enables the scanner to emulate a keyboard's output in different languages. To ensure the keyboard layout matches the language code page of the output data, it is necessary to set a correct corresponding code page using the **Keyboard Output Country Code Page** function.

- Refer to the **Appendix: Code Page - Table of Corresponding Languages** for more details about the code page of each language.
- When the **Universal** keyboard layout is selected, ASCII characters are transmitted using 'Alt Code outputs,' simulating a combination of the 'Alt' key with a series of numeric keypad inputs. For instance, the uppercase letter 'A' is transmitted as 'Alt + 0 0 6 5' in the Universal keyboard.
- The Universal keyboard layout is exclusively available for the Windows operating system.



Keyboard Encoding Country Code Page




Program

2D ONLY

Family Code	PP	Parameter Selection		Option Code	
 <p>Keyboard Encoding Country Code Page</p>	MS	UTF8	ISO 8859-1 Latin 1, West Euro	00	1E
	MS	Code page 950	ISO 8859-2 Latin 2, Central Euro	10	1F
	MS	Code page 949	ISO 8859-3 Latin 3, South Euro	11	20
	MS	Code page 936	ISO 8859-4 Latin 4, North Euro	12	21
	MS	Code page 932	ISO 8859-5 Cyrillic	13	22
	MS	Code page 874	ISO 8859-6 Arabic	14	23
	MS	WIN1250	ISO 8859-7 Greek	15	24
	MS	WIN1251	ISO 8859-8 Hebrew	16	25
	MS	WIN1252 ◀	ISO 8859-9 Latin 5, Turkish	17	26
	MS	WIN1253	ISO 8859-10 Latin 6, Nordic	18	27
	MS	WIN1254	ISO 8859-11 Thai	19	28
	MS	WIN1255	ISO 8859-13 Latin 7, Baltic	1A	29
	MS	WIN1256	ISO 8859-14 Latin 8, Celtic	1B	2A
	MS	WIN1257	ISO 8859-15 Latin 9	1C	2B
	MS	WIN1258	ISO 8859-16 Latin 10, SE Euro	1D	2C

Keyboard Encoding Country Code Page configures which code page the scanner uses when decoding 2D barcodes.

- Select **UTF8** if the 2D barcode is encoded in Unicode (UTF8).
- Make sure that the decoding code page matches the original encoding code page for the correct output. Refer to **Appendix: Code Page - Table of Corresponding Languages** for details about the code page of each language.



Keyboard Output Country Code Page




Program

2D ONLY

Family Code	PP	Parameter Selection		Option Code	
 <p>Keyboard Output Country Code Page</p>	MS	MAC Unicode	Code Page 855	01	31
	MS	WIN Notepad Unicode	Code Page 866	02	32
	MS	WIN WordPad Unicode	Code Page 850	03	33
	MS	Code Page 950	Code Page 437	10	34
	MS	Code Page 949	Code Page 737	11	35
	MS	Code Page 936	Code Page 857	12	36
	MS	Code Page 932	Code Page 862	13	37
	MS	Code Page 874	Code Page 720	14	38
	MS	WIN1250	Code Page 775	15	39
	MS	WIN1251	WIN1255	16	1A
	MS	WIN1252 ◀	WIN1256	17	1B
	MS	WIN1253	WIN1257	18	1C
	MS	WIN1254	WIN1258	19	1D
	MS	Code Page 852		30	

Keyboard Output Country Code Page controls which code page the scanner uses when it transmits the scanned data. Make sure that the output format matches the decoding format (**Encoding Country Code Page**) and language setting of the operating system on the host device.

- **Mac Device output:** Select “MAC Unicode Output” on the scanner, and select “Unicode Hex Input” as the input format on the MAC device with a 16-bit input setup. See **Appendix: Code Page - Unicode Hex Input Setup** for the setup process.
- **WIN Notepad Unicode output:** When outputting Unicode barcodes to Notepad, select “Unicode Hex Input” and set English (United States) as the system language on the host device. See **Appendix: Code Page - Unicode Hex Input Setup** for the setup process.
- **WIN WordPad Unicode output:** When outputting Unicode barcodes to WordPad, set English (United States) as the system language on the host device.



Alt Code Digit Control




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 Alt Code Digit Control	SS	Transmit Alt Code with 3 digits	0
	SS	Transmit Alt Code with 4 digits ◀	1

Alt Code Digit Control configures how the scanner sends out ASCII codes using Alt Code output (The combination of modifier key “Alt” with several numeric keypad inputs):

- **Transmit Alt Code with 3 digits:** When selected, the scanner sends out the Alt Codes containing 3 numeric digits. For instance, the uppercase letter “A” is transmitted as “Alt + 0 6 5”.
- **Transmit Alt Code with 4 digits:** When selected, the scanner sends out Alt Codes containing 4 numeric digits. For instance, the uppercase letter “A” is transmitted as “Alt + 0 0 6 5”.



Alt Code Break Control




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 Alt Code Break Control	SS	Transmit Alt Code with BREAK keys	0
	SS	Transmit Alt Code without BREAK keys ◀	1

Alt Code Break Control configures the detail of key strokes when the scanner sends out ASCII codes using Alt Code output (The combination of modifier key “Alt” with several numeric keypad inputs):

- Transmit Alt Code with BREAK keys:** When selected, the scanner sends out the Alt Codes with complete key strokes. For instance, when the scanner sends out uppercase letter “A” (Alt + 0 0 6 5), it sequentially sends out the key string “[Alt(MAKE)] [0(MAKE)] [0(BREAK)] [0(MAKE)] [0(BREAK)] [6(MAKE)] [6(BREAK)] [5(MAKE)] [5(BREAK)] [Alt(BREAK)].
- Transmit Alt Code without BREAK keys:** When selected, the scanner omits the BREAK keys to speed up the transmission of the Alt Codes. For instance, when the scanner sends out uppercase letter “A” (Alt + 0 0 6 5), it sequentially sends out the key string “[Alt(MAKE)] [0(MAKE)] [0(MAKE)] [6(MAKE)] [5(MAKE)] [Alt(BREAK)]. This option enables the scanner to transmit Alt Codes more quickly but increases the likelihood of incompatibility with certain operating systems. Disable this function if you encounter difficulties sending Alt Codes.



User-defined Function Key




Program

ALL

Family Code	PP	Parameter Selection	OC 1	OC 2
 User-defined Function Key	DS	Set output character [OC2] to value [OC1]	[00-1F]	(4 digits)

- **User-defined Function Key** enables the scanner to transmit special characters not defined in standard ASCII table. Follow the step below to output the desired characters:
 - Refer to **Appendix - Function Key Character Table**, choose a special character from the table, and assign its corresponding **4-digit Option Code** to any of the 32 function key slots with hex value identifiers between 00 and 1F. For example, scan [User-defined Function Key] [00] [003A] to assign function key character “F1” to slot 00.
 - The scanner can transmit the special character you defined when it reads a barcode containing the data value you defined.
 - Or you can enter the defined special character in the same way as you may enter other standard ASCII characters.
 - It is highly recommended to use the **PowerTool 3** software utility to set the Function Keys.
 - To guarantee the accuracy of the user-defined function keys, configure the **Keyboard Country Layout** to the **USA (QWERTY)** layout.
- Refer to Appendix - Function Key Character Table for a complete list of selectable characters.
- Refer to Appendix - Function Key Output Table for the default characters of the 32 Function Keys.



USB Data Merge

2D ONLY




Program

Family Code	PP	Parameter Selection	Option Code
 USB Data Merge	SS	Disable ◀	0
	SS	Enable	1

USB Data Merge: When enabled, the decoded characters of the same barcode can be packed into fewer data packets to increase transmitting speed. Be aware that enabling data merge may lead to higher data loss possibility. Disable this function if you have connection difficulties.

- For all scanners, USB Data Merge is not available on macOS nor on iOS.
- For the A and PA series Bluetooth scanners, the Data Merge function is not available under Bluetooth SPP modes.



USB Legacy mode




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 USB Legacy Mode	SS	Disable ◀	0
	SS	Enable	1

USB Legacy Mode: When enabled, the scanner communicates with the host via USB HID interface. When disabled, the scanner communicates with the host via USB composite interface for enhanced functionality. One interface can function as a USB HID, while another can act as a USB Serial for more advanced communication with the host.



Modifier Key Output Control




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 Modifier Key Output Control	SS	MAKE key + BREAK key output ◀	0
	SS	Composite output	1

Modifier Key Output Control determines how the scanner outputs data when the modifier key is used in combination with another non-modifier key.

- **MAKE key + BREAK key:** The scanner outputs data in a manner that simulates the sequential input of keystrokes. For example, if modifier key “SHIFT” is scanned together with numeric key “5”, the outcome would be SHIFT(MAKE) + SHIFT(BREAK) + 5(MAKE) + 5(BREAK).
- **Composite output:** The scanner generates output that mimics simultaneous pressing of the modifier key with the initial input key. For instance, when scanning the modifier key “SHIFT” alongside the numeric key “5,” the result would be SHIFT(MAKE) + 5(MAKE) + 5(BREAK) + SHIFT(BREAK).



2.3 Serial Interface Settings

This section provides the command barcodes for configuring the serial interface of your scanner. You can find the functional details of each command barcode and specified parameter selection.

STX/ETX Transmit



Program


ALL

Family Code	PP	Parameter Selection	Option Code
 STX/ETX Transmit	SS	Disable ◀	0
	SS	Enable	1

STX/ETX Transmit: When enabled, the scanner transmits invisible STX and ETX characters under the serial interface. STX and ETX are characters used to indicate the start and end of a total data frame.

The table below shows the complete **Serial Interface Message String (RS232, USB COM)**:

STX	Preamble	Scanned Data Length	Prefix Code ID	Scanned Data	Suffix Code ID	Postamble	ETX	Record Suffix
1 char.	1-15 char.	2-4 digits	1 or 3 char.	Variable length	1 or 3 char.	1-15 char.	1 char.	1 char.



Serial Record Suffix




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 <p>Serial Record Suffix</p>	SS	None	0
	SS	CR (0Dh) ◀	1
	SS	LF (0Ah)	2
	SS	CRLF (0Dh 0Ah)	3
	SS	TAB (09h)	4
	SS	SPACE (20h)	5
	MS	User-defined character (1 character)	6, (00-7F)

The table below shows the complete **Serial Interface Message String (RS232, USB COM)**:

STX	Preamble	Scanned Data Length	Prefix Code ID	Scanned Data	Suffix Code ID	Postamble	ETX	Record Suffix (Serial)
1 char.	1-15 char.	2-4 digits	1 or 3 char.	Variable length	1 or 3 char.	1-15 char.	1 char.	1 char.




Serial Intermessage Delay




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 Serial Intermessage Delay	SS MS	None ◀ 1-99 (x5) ms	FIN (2 digits)

- **Serial Intermessage Delay** is the time delay between messages transmitted by the scanner. Increasing this delay will help host applications process the incoming data on time.
- For the A, F, L, and PA, PF, PL series Bluetooth scanners, Serial Intermessage Delay is not available under Bluetooth SPP and Bluetooth HID modes.
- After scanning the 2 digits, the selection ends automatically.



Serial Intercharacter Delay




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 Serial Intercharacter Delay	SS	None ◀	FIN
	MS	1-99 (x5) ms (All corded series)	(2 digits)
	MS	1-99 (x10) ms (All Bluetooth series)	(2 digits)

- Serial Intercharacter Delay is the time delay between characters transmitted by the scanner. This parameter is used to synchronize data communication when:
 - Data transmission speed is too fast, causing characters to be skipped;
 - Multitasking operation system or host computers in a network may slow down keyboard handling;
 - Various notebook or desktop PC systems require different timing configurations.
- Add one extra unit as safety margin
- For the A, F, L, and PA, PF, PL series Bluetooth scanners, Serial Intercharacter Delay is not available under Bluetooth SPP and Bluetooth HID modes.
- After scanning the 2 digits, the selection ends automatically.



Serial Interfunction Delay




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 Serial Interfunction Delay	SS MS	None ◀ 1-99 (x5) ms	FIN (2 digits)

- Serial Interfunction Delay is the time delay between two data segments divided by a function character.
- For the A, F, L, and PA, PF, PL series Bluetooth scanners, Serial Interfunction Delay is not available under Bluetooth SPP and Bluetooth HID modes.
- After scanning the 2 digits, the selection ends automatically.



Handshaking Protocol




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 Handshaking Protocol	SS	None ◀	0
	SS	RTS/CTS hardware handshaking	1
	SS	ACK/NAK software handshaking	2
	SS	XON/XOFF software handshaking	3

Handshaking Protocol configures which protocol is adapted by the scanner to communicate with the host device.

- USB CDC/Virtual COM does not support the RTS/CTS handshaking protocol.
- For A, F, L, and PA, PF, PL series Bluetooth models, the ACK/NAK handshaking protocol is available with:
 - **Pair mode**, using RS232 or USB CDC/Virtual COM interface.
 - **SPP master or slave mode**.
- **None:** When selected, the scanner transmits data whenever it decodes a barcode.
- **RTS/CTS hardware handshaking:** When selected, the scanner sends out RTS (request to send) and CTS (clear to send) signals before normal data communication begins. This protocol can ensure the reliability of data transmission.
- **ACK/NAK software handshaking:** When selected, the scanner waits for an ACK (acknowledgement) or NAK (negative acknowledgement) character sent from the host device after each data transmission. If it receives a NAK, the scanner re-sends the data until receiving an ACK.
- **XON/XOFF software handshaking:** When selected, the scanner waits for an XON (transmit on) or XOFF (transmit off) character sent from the host device after each data transmission.



Response/Baud Rate/Data Frame




Program

ALL

Family Code	PP	Parameter Selection		Option Code	
<p>Response Timeout</p>	SS	None	3 sec	0	6
	SS	200 ms	4 sec	1	7
	SS	500 ms ◀	5 sec	2	8
	SS	800 ms	8 sec	3	9
	SS	1 sec	10 sec	4	A
	SS	2 sec	15 sec	5	B
	<p>Baud Rate</p>	SS	38.4K BPS	1200 BPS	0
SS		19.2K BPS	57.6K BPS	1	8
SS		9600 BPS ◀	115.2K BPS	2	9
SS		4800 BPS	230.4K BPS	3	A
		2400 BPS		4	
<p>Data Frame</p>	SS	8, None, 1 ◀	7, Space, 1	0	8
	SS	8, Odd, 1	7, Mark, 1	1	9
	SS	8, Even, 1	7, None, 2	2	A
	SS	8, Space, 1	7, Odd, 2	3	B
	SS	8, Mark, 1	7, Even, 2	4	C
	SS	8, None, 2	7, Space, 2	5	D
	SS	7, Odd, 1	7, Mark, 2	6	E
	SS	7, Even, 1		7	

- **Response Timeout** configures how long the scanner waits for an ACK or NAK response from the host device before it discards the decoded data and issues an error indication.
- The baud rate of 1200BPS is not supported by 1D scanners firmware version 6.00.14 and later.



Serial Encoding Country Code Page




Program

2D ONLY

Family Code	PP	Parameter Selection		Option Code	
 <p>Serial Encoding Country Code Page</p>	MS	UTF8	ISO 8859-1 Latin 1, West Euro	00	1E
		Code Page 950	ISO 8859-2 Latin 2, Central Euro	10	1F
		Code Page 949	ISO 8859-3 Latin 3, South Euro	11	20
		Code Page 936	ISO 8859-4 Latin 4, North Euro	12	21
		Code Page 932	ISO 8859-5 Cyrillic	13	22
		Code Page 874	ISO 8859-6 Arabic	14	23
		WIN1250	ISO 8859-7 Greek	15	24
		WIN1251	ISO 8859-8 Hebrew	16	25
		WIN1252 ◀	ISO 8859-9 Latin 5, Turkish	17	26
		WIN1253	ISO 8859-10 Latin 6, Nordic	18	27
		WIN1254	ISO 8859-11 Thai	19	28
		WIN1255	ISO 8859-13 Latin 7, Baltic	1A	29
		WIN1256	ISO 8859-14 Latin 8, Celtic	1B	2A
		WIN1257	ISO 8859-15 Latin 9	1C	2B
		WIN1258	ISO 8859-16 Latin 10, SE Euro	1D	2C

Serial Encoding Country Code Page configures which code page the scanner uses when decoding 2D barcodes. Make sure that the decoding format matches the original encoding format for the correct output.

- Select **UTF8** if the 2D barcode is encoded in Unicode (UTF8).
- Refer to **Appendix: Code Page - Table of Corresponding Languages** for details about the code page of each language.



Serial Output Country Code Page


2D ONLY



Program

Family Code	PP	Parameter Selection		Option Code	
 <p>Serial Output Country Code Page</p>	MS	Raw data ◀	WIN1257	00	1C
		Unicode (Big Endian)	WIN1258	01	1D
		Unicode (Little Endian)	Code Page 852	02	30
		UTF8	Code Page 855	03	31
		Code Page 950 (Big Endian)	Code Page 866	10	32
		Code Page 949 (Big Endian)	Code Page 850	11	33
		Code Page 936 (Big Endian)	Code Page 437	12	34
		Code Page 932 (Big Endian)	Code Page 737	13	35
		Code Page 874	Code Page 857	14	36
		WIN1250	Code Page 862	15	37
		WIN1251	Code Page 720	16	38
		WIN1252	Code Page 775	17	39
		WIN1253	Code Page 950 (Little Endian)	18	90
		WIN1254	Code Page 949 (Little Endian)	19	91
		WIN1255	Code Page 936 (Little Endian)	1A	92
		WIN1256	Code Page 932 (Little Endian)	1B	93

Serial Output Country Code Page configures the data format when transmitting decoded data. For the correct output in the desired language, make sure that this setting matches the original encoding format (Encoding Country Code Page).



Serial NAK Retry Count




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 NAK Retry Count	SS	3 times ◀	FIN
	SS	Disable	000
	SS	1-254 times	(3 digits)
	SS	Retry unlimited times	255

NAK Retry Count configures how many times the scanner resends decoded data after receiving a NAK response. The scanner issues an error indication and discards decoded data if:

- The number of resend reaches the limit set by NAK Retry Count.
- The preset **Serial Response Timeout** is up before the NAK retry count reaches its limit.
- When disabled, the scanner discards the decoded data upon receiving a NAK.
- For the A, F, L, PA, PF, and PL series Bluetooth scanners, NAK Retry Count is not available under Batch Scanning mode. Enabling NAK Retry Count automatically disables out-of-range scanning under online (normal) scanning mode.



ACK Indication




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 <p>ACK Indication</p>	SS	Disable ACK indication; disable ACK timeout indication	0
	SS	Disable ACK indication; enable ACK timeout indication ◀	1
	SS	Enable ACK indication; disable ACK timeout indication	2
	SS	Enable ACK indication; enable ACK timeout indication	3

- **ACK Timeout Indication:** When enabled, the scanner emits LED and beeping indications once the Serial Response Timeout is up.
- **ACK Indication:** When enabled, the scanner emits LED and beeping indications once it receives an ACK response.



3 Barcode Reading

This chapter contains the parameters that will help users set up their scanners to read different types of barcodes supported by FuzzyScan scanners. Corresponding detailed settings of each code type are also collected in this chapter. Users can enable the Barcode ID function to identify the type of code scanned.

3.1 Code ID

This section provides the command barcodes for configuring the type of suffix and character to be transmitted by your scanner upon a good read. You can find the functional details of each command barcode and specified parameter selection.

Code ID Transmit



Program

ALL

Family Code	PP	Parameter Selection	Option Code
 <p>Code ID Transmit</p>	SS	Disable ◀	0
	SS	Transmit Cino ID as prefix	1
	SS	Transmit Cino ID as suffix	2
	SS	Transmit Cino ID as prefix and suffix	3
	SS	Transmit AIM ID as prefix	4
	SS	Transmit AIM ID as suffix	5
	SS	Transmit AIM ID as prefix and suffix	6


Code ID Transmit: When enabled, the scanner sends out an ID alongside the data value to identify the type of scanned barcode. Code ID can be transmitted either as a prefix, a suffix, or both. Refer to **Appendix - Code ID Table** for a complete list of Cino ID or AIM ID.

The table below shows the complete **Keyboard Interface Message String (USB HID):**

Preamble	Scanned Data Length	Prefix Code ID	Scanned Data	Suffix Code ID	Postamble	Record Suffix (KB)
1-15 char.	2-4 digits	1 or 3 char.	Variable length	1 or 3 char.	1-15 char.	1 char.

The table below shows the complete **Serial Interface Message String (RS232, USB COM):**

STX	Preamble	Scanned Data Length	Prefix Code ID	Scanned Data	Suffix Code ID	Postamble	ETX	Record Suffix (Serial)
1 char.	1-15 char.	2-4 digits	1 or 3 char.	Variable length	1 or 3 char.	1-15 char.	1 char.	1 char.



Code ID - 1 Character




Program

ALL

Family Code	PP	Parameter Selection	OC1	OC2	PP	Parameter Selection	OC1	OC2
 Code ID - 1 Character	DS	Code 128 (B)	00	1 ch	DS	China Postal Code (L)	10	1 ch
	DS	GS1 128 (C)	01	1 ch	DS	German Postal Code (M)	11	1 ch
	DS	UPC A (A)	02	1 ch	DS	IATA (O)	12	1 ch
	DS	EAN 13 (F)	03	1 ch	DS	Code 11 (P)	13	1 ch
	DS	Codabar (D)	04	1 ch	DS	MSI (R)	14	1 ch
	DS	Code 39/Code 32 (G)	05	1 ch	DS	UK/Plessey (S)	15	1 ch
	DS	Code 93 (H)	06	1 ch	DS	Telepen (T)	16	1 ch
	DS	Industrial 25 (I)	07	1 ch	DS	GS1 DataBar (X)	17	1 ch
	DS	Interleaved 25 (J)	08	1 ch	DS	UPC E (E)	18	1 ch
	DS	Matrix 25 (K)	09	1 ch	DS	EAN 8 (N)	19	1 ch

- Code ID - 1 Character replaces the 1-character Cino ID from its default to the user-defined value.
- To scan the 2nd option code, refer to the HEX to ASCII Conversion Table below:

L \ H	0	1	2	3	4	5	6	7
0	NUL	DLE	SPACE	0	@	P	`	p
1	SOH	DC1	!	1	A	Q	a	q
2	STX	DC2	*	2	B	R	b	r
3	ETX	DC3	#	3	C	S	c	s
4	EOT	DC4	\$	4	D	T	d	t
5	ENQ	NAK	%	5	E	U	e	u
6	ACK	SYN	&	6	F	V	f	v
7	BEL	ETB	'	7	G	W	g	w
8	BS	CAN	(8	H	X	h	x
9	HT	EM)	9	I	Y	i	y
A	LF	SUB	*	:	J	Z	j	z
B	VT	ESC	+	;	K	[k	{
C	FF	FS	.	<	L	\	l	
D	CR	GS	-	=	M]	m	}
E	SO	RS	.	>	N	^	n	~
F	SI	US	/	?	O	_	o	DEL



Code ID - 1 Character (continued)



Program

ALL

Family Code	PP	Parameter Selection	OC1	OC2	PP	Parameter Selection	OC1	OC2
 Code ID - 1 Character	DS	Trioptic Code 39 (W)	20	1 ch	DS	Australian Post (g)	33	1 ch
	DS	UCC Coupon Ext. Code (Z)	21	1 ch	DS	British Post (h)	34	1 ch
	DS	PDF417/Micro PDF417 (V)	22	1 ch	DS	Intelligent Mail (USPS 4CB) (j)	36	1 ch
	DS	Korea Post Code (a)	26	1 ch	DS	Japan Post (k)	37	1 ch
	DS	QR/Micro QR Code (b)	28	1 ch	DS	Netherlands KIX Post (l)	38	1 ch
	DS	Data Matrix (c)	29	1 ch	DS	US Planet (m)	39	1 ch
	DS	Maxi Code (d)	30	1 ch	DS	US Postnet (o)	41	1 ch
	DS	Aztec Code (e)	31	1 ch	DS	Posi LAPA code (q)	43	1 ch

To scan the 2nd option code, refer to the HEX to ASCII Conversion Table below:

L \ H	0	1	2	3	4	5	6	7
0	NUL	DLE	SPACE	0	@	P	`	p
1	SOH	DC1	!	1	A	Q	a	q
2	STX	DC2	*	2	B	R	b	r
3	ETX	DC3	#	3	C	S	c	s
4	EOT	DC4	\$	4	D	T	d	t
5	ENQ	NAK	%	5	E	U	e	u
6	ACK	SYN	&	6	F	V	f	v
7	BEL	ETB	'	7	G	W	g	w
8	BS	CAN	(8	H	X	h	x
9	HT	EM)	9	I	Y	i	y
A	LF	SUB	*	:	J	Z	j	z
B	VT	ESC	+	;	K	[k	{
C	FF	FS	.	<	L	\	l	
D	CR	GS	-	=	M]	m	}
E	SO	RS	.	>	N	^	n	~
F	SI	US	/	?	O	_	o	DEL

OPTION CODE


0


4


7


9


C


1


5


8


A


D


2


6


B


E


3


FIN


F


END


FACTORY DEFAULT

3.2 Barcode Readability

This section provides the command barcode for configuring the type of symbologies to be recognized and decoded by your scanner. You can find the functional details of each specified parameter selection.

Readable Barcode Settings




Program

ALL

Family Code	PP		Parameter Selection		Option Code	
 <p>Readable Barcode</p>	SS	CS	Auto ◀	MSI	00	11
	CS	CS	Popular 1D	UK/Plessey	C0	12
	CS	CS	Code 128 *	Telepen	01	13
	CS	CS	GS1 128 *	GS1 DataBar *	31	14
	CS	CS	UPC A *	IATA	02	15
	CS	CS	UPC E *	PDF417 */Micro PDF417	03	17
	CS	CS	EAN 13 *	Korea Post Code	04	21
	CS	CS	EAN 8 *	QR Code */Micro QR Code *	05	A0
	CS	CS	Codabar *	Data Matrix *	06	A1
	CS	CS	Code 39 *	MaxiCode	07	A2
	CS	CS	Trioptic Code 39	Aztec Code *	47	A3
	CS	CS	Industrial 25	Australian Post	08	B0
	CS	CS	Matrix 25	British Post	38	B1
	CS	CS	Interleaved 25 *	Intelligent Mail	48	B3
	CS	CS	China Postal Code	Japan Post	58	B4
	CS	CS	German Postal Code	KIX Post	68	B5
	CS	CS	Code 93 *	US Planet Code	09	B6
	CS	CS	Code 11	US Postnet	10	B8

Readable Barcode Settings configures which code type(s) can be recognized and decoded by the scanner. Reducing readable barcode types improves reading speed and lowers the possibility of reading errors.




Readable Barcode Settings (continued)



Program

ALL

- **Auto:** When selected, the scanner only reads commonly used 1D and 2D barcode types marked with an asterisk in the table above.
- **Popular 1D:** When selected, the scanner stops reading 2D barcodes and only reads commonly used 1D barcodes including Code 128, GS1 128, UPC A, UPC E, EAN 13, EAN 8, Codabar, Code 39, Interleaved 25, Code 93, and GS1 DataBar.
- When the scanner is configured to stop reading 2D barcode types, reading speed and accuracy for all 1D barcode types will massively increase.
- Entering **“Auto”** ends the process automatically. For other options, scan **“FIN”** to end the process.



3.3 Barcode Settings

This section provides the command barcodes for configuring the type of barcodes to be recognized by your scanner. You can find the details of specified parameter selections under each command barcode.

Code 39/32, Trioptic Code 39




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 Code 39/32 Readability	SS	Disable	0
	SS	Enable ◀	1
 Trioptic C39 Readability	SS	Disable ◀	0
	SS	Enable	1

- Only supports Trioptic Code 39 with 6 characters.
- **DO NOT** select “Full ASCII Code 39” in Code 39 Primary Format when enabling Trioptic Code 39.



Code 39


ALL



Program

Family Code	PP	Parameter Selection	Option Code
 C39 Primary Format	SS	[New] Standard Code 39 ◀	2
	SS	[New] Full ASCII Code 39	3
	SS	Code 32 (PARAF, Italian Pharmaceutical)	4
 C39 Start/Stop Transmit	SS	[New] Disable ◀	5
	SS	[New] Enable	6
 C32 Leading A Transmit	SS	[New] Disable ◀	7
	SS	[New] Enable	8

- **Standard Code 39:** When selected, the scanner decodes Code 39 with standard character sets consisting of numeric digits 0 - 9, uppercase letters A - Z, and special characters including the percent sign (%), plus sign (+), .dollar sign (\$), slash (/), period (.) and hyphen (-).
- **Full ASCII Code 39:** When selected, the scanner decodes Code 39 with all 128 ASCII characters. The scanner treats certain pairs of special character and alphabet as a single ASCII character and transmits it. **Do not** enable Trioptic Code 39 with this option.
- **Code 32:** When selected, the scanner decodes Code 39 following the coding rule of Code 32 (also known as PARAF) commonly used by the Italian pharmaceutical industry.
- **Code 39 Start/Stop Transmit:** When enabled, the scanner transmits additional asterisk (*) characters to mark the beginning and the end of a Code 39.
- **Code 32 Leading A Transmit:** When enabled, the scanner transmits the leading character “A” which is normally skipped.



Code 39 (continued)




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 C39 Check Digit Verify	SS SS	Disable ◀ Enable	9 A
 C39 Check Digit Transmit	SS SS	Disable ◀ Enable	B C
 C39 Buffering	SS SS	Disable ◀ Enable	D E

- **Code 39 Check Digit Verify:** When enabled, the scanner only decodes Code 39 conforming to the MOD 43 checksum rule.
- **Code 39 Check Digit Transmit:** When enabled, the scanner transmits additional checksum digits that are normally skipped.
- **Code 39 Buffering:** When enabled, the scanner temporarily stores multiple Code 39 data in its buffer memory and transmits the data all together. When disabled, the scanner transmits each Code 39 data immediately.



Code 39 (continued)




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 C39 Minimum Length	SS MS	Default (01) ◀ 01-Maximum	FIN (2 digits)
 C39 Maximum Length	SS MS	Default (98) ◀ 98-Minimum	FIN (2 digits)
 C39 Security Level	SS SS SS SS	Level 0 Level 1 Level 2 ◀ Level 3	0 1 2 3

- For **Code 39 Minimum Length** and **Maximum Length**, the data length excludes start/stop characters, such as the barcode ID.
- **Code 39 Security Level** configures how well the scanner decodes poorly-printed or out-of-spec barcodes. Among the available levels, Level 1 has the highest level of sensitivity, but also the highest chance of a misread.
- **Code 39 Security Level** is only available on 1D scanners.
- After scanning the 2 digits, the selection ends automatically.



Code 93




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 Code 93 Readability	SS SS	Disable Enable ◀	0 1
 C93 Check Digit Transmit	SS SS	Disable ◀ Enable	2 3
 C93 Minimum Length	SS MS	Default (01) ◀ 01-Maximum	FIN (2 digits)
 C93 Maximum Length	SS MS	Default (98) ◀ 98-Minimum	FIN (2 digits)

- For Code 93 Minimum Length and Maximum Length, the data length excludes start/stop characters, such as the barcode ID.
- After scanning the 2 digits, the selection ends automatically.



Code 128

ALL




Program

Family Code	PP	Parameter Selection	Option Code
 Code 128 Readability	SS	Disable Code 128	0
	SS	Enable Code 128 ◀	1
 C128 ISBT Concatenate	SS	Disable ISBT Concatenation ◀	2
	SS	Enable ISBT Concatenation	3
	SS	Enable ISBT Concatenation with table check	4
	SS	Enable ISBT Concatenation Auto	5

Code 128 ISBT Concatenate configures how the scanner reacts when it reads International Society of Blood Transfusion (ISBT) barcodes.

- **Disable ISBT Concatenation:** The scanner does not transmit any ISBT concatenated barcodes.
- **Enable ISBT Concatenation:** The scanner only decodes and transmits ISBT concatenated barcodes. The scanner does not decode any single (unconcatenated) ISBT barcode.
- **Enable ISBT Concatenation with table check:** The scanner only decodes and transmits concatenated ISBT barcodes which conform to ICCBBA standards and are listed in the Standard Technical Specification check table. The scanner does not decode any single ISBT barcode or ISBT concatenated barcode not conforming to ICCBBA standards.
- **Enable ISBT Concatenation Auto:** The scanner decodes and transmits both ISBT concatenated barcodes and single ISBT barcodes.





Code 128 (continued)




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 C128 Minimum Length	SS MS	Default (01) ◀ 01-Maximum	FIN (2 digits)
 C128 Maximum Length	SS MS	Default (98) ◀ 98-Minimum	FIN (2 digits)
 C128 Security Level	SS SS	Level 0 Level 1 ◀	0 1


- For Code 128 Minimum Length and Maximum Length, the data length excludes start/stop characters, such as the barcode ID.
- Code 128 Security Level configures how the scanner decodes poorly-printed or out-of-spec barcodes. Level 1 has the highest level of sensitivity allowing faster scanning on in-spec barcodes, while Level 0 is used for reading poorly-printed or out-of-spec barcodes to avoid misreading.
- Code 128 Security Level is only available on 1D scanners.
- After scanning the 2 digits, the selection ends automatically.





Family Code	PP	Parameter Selection	Option Code
 Codabar Readability	SS	Disable	0
	SS	Enable ◀	1
 Codabar Primary Format	SS	Standard format ◀	2
	SS	ABC format	3
	SS	CLSI format	4
	SS	CX format	5
 Codabar Start/Stop Transmit	SS	Disable ◀	6
	SS	Transmit as ABCD/ABCD	7
	SS	Transmit as abcd/abcd	8
	SS	Transmit as ABCD/TN*E	9
	SS	Transmit as abcd/tn*e	A

- **Codabar Readability:** When enabled, the scanner recognizes and decodes Codabar barcodes.
- **Codabar Primary Format** configures which Codabar format or concatenating rule the scanner follows.
- **Codabar Start/Stop Transmit:** When enabled, the scanner converts the STX and ETX characters of a Codabar code into the selected format, and transmits them out with the decoded data.






Program

ALL

Family Code	PP	Parameter Selection	Option Code
 Codabar Check Digit Verify	SS SS	Disable ◀ Enable	B C
 Codabar Check Digit Select	SS SS SS SS SS SS SS	Modulus 16 ◀ Modulus 10/Weight 3 Modulus 11 Modulus 10/Weight 2 7 check DR Weight Modulus 11 Runes (Modulus 10/Weight 2)	0 1 2 3 4 5 6
 Codabar Check Digit Transmit	SS SS	Disable ◀ Enable	D E



Codabar (continued)




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 Codabar Minimum Length	SS MS	Default (04) ◀ 01 to Maximum	FIN (2 digits)
 Codabar Maximum Length	SS MS	Default (98) ◀ Minimum to 98	FIN (2 digits)

- For **Codabar Minimum Length** and **Maximum Length**, the data length excludes start/stop characters, such as the barcode ID.
- After scanning the 2 digits, the selection ends automatically.



UPC




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 UPC A Readability	SS SS	Disable Enable ◀	0 1
 UPC E Readability	SS SS	Disable Enable ◀	2 3
 UPC E Expansion	SS SS	Disable ◀ Enable	4 5
 UPC Standardization	SS SS	Disable ◀ Enable	6 7

- **UPC E Expansion:** When enabled, the decoded 8-digit UPC E is converted into a 12-digit UPC A and is affected by related settings, such as UPC standardization, UPC numeric system, and UPC A check digit transmission.
- **UPC Standardization:** When enabled, the scanner expands 12-digit UPC A to 13-digit EAN 13 by inserting an extra zero.

WPC Selection (UPC/EAN/CAN)	Basic Length	Disable Check Digit	Disable Numeric System	2-digit Addendum	5-digit Addendum	Enable Standardization	Enable Expansion
UPC A	12	- 1	- 1	+ 2	+ 5	+ 1	0
UPC E	8	- 1	- 1	+ 2	+ 5	+ 1	+ 4
EAN 13	13	- 1	NC	+ 2	+ 5	NC	0
EAN 8	8	- 1	NC	+ 2	+ 5	NC	+ 5



UPC (continued)




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 UPC Numeric System	SS SS	Disable Enable ◀	8 9
 UPC A Check Digit Transmit	SS SS	Disable Enable ◀	A B
 UPC E Check Digit Transmit	SS SS	Disable Enable ◀	C D
 UPC E1 Readability	SS SS	Disable ◀ Enable	E F

UPC E1 Readability: When enabled, the scanner recognizes and transmits UPC E1 codes with “1” as the first digit.

WPC Selection (UPC/EAN/CAN)	Basic Length	Disable Check Digit	Disable Numeric System	2-digit Addendum	5-digit Addendum	Enable Standardization	Enable Expansion
UPC A	12	- 1	- 1	+ 2	+ 5	+ 1	0
UPC E	8	- 1	- 1	+ 2	+ 5	+ 1	+ 4
EAN 13	13	- 1	NC	+ 2	+ 5	NC	0
EAN 8	8	- 1	NC	+ 2	+ 5	NC	+ 5






Program

ALL

Family Code	PP	Parameter Selection	Option Code
 UPC Supplement Digits Select	SS	Ignore supplement digits ◀	0
	SS	UPC with 2-digit supplement	1
	SS	UPC with 5-digit supplement	2
	SS	UPC with 2- or 5-digit supplement	3
 Force UPC Supplement Digits Output	SS	Disable ◀	4
	SS	Enable	5
 UPC Addenda Separator	SS	Disable ◀	6
	SS	Enable	7

- **UPC Supplement Digits Select** configures which type of UPC code the scanner decodes according to its supplement digit format.
- **UPC Supplement Digits Output:** When enabled, the scanner transmits the UPC type specified by **UPC Supplement Digit Select** together with its supplement digits.
- **UPC Addenda Separator:** With **UPC Supplement Digits Output** enabled and matching supplement digit format, enable this function to insert a space between the main UPC code and its supplement digits upon data transmission.






Program

ALL

Family Code	PP	Parameter Selection		Option Code	
 UPC A Security Level	SS	Level 0		0	
	SS	Level 1 ◀		1	
	SS	Level 2		2	
 UPC Supplement Scan Voting	SS	None	Level 7	0	7
	SS	Level 1	Level 8	1	8
	SS	Level 2	Level 9	2	9
	SS	Level 3 ◀	Level 10	3	A
	SS	Level 4	Level 11	4	B
	SS	Level 5	Level 12	5	C
	SS	Level 6	Level 13	6	D

- **UPC A Security Level** configures how the scanner decodes poorly-printed or out-of-spec UPC A barcodes. Level 2 has the highest level of sensitivity among the available levels. At Level 2, the scanner decodes barcodes quickly, but easily misreads barcodes, especially character numbers 1, 2, 7, and 8.
- **UPC A Security Level** is only available on 1D scanners.
- **UPC Supplement Scan Voting** determines how many times an UPC/EAN with 2/5 supplement digits has to be decoded before output. Supplement Scan Voting is valid for UPC/EAN with only 2 supplement digits, UPC/EAN with only 5 supplement digits, or UPC/EAN with 2 or 5 supplement digits. Selecting a higher level might slow down the scanner when it reads poorly-printed, low contrast, or damaged barcodes.



EAN




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 EAN 13 Readability	SS SS	Disable Enable ◀	0 1
 EAN 8 Readability	SS SS	Disable Enable ◀	2 3
 EAN 8 Expansion	SS SS	Disable ◀ Enable	4 5

- **EAN 8 Expansion:** When enabled, the scanner converts 8-digit EAN 8 to 13-digit EAN 13 and transmits it out.

WPC Selection (UPC/EAN/CAN)	Basic Length	Disable Check Digit	Disable Numeric System	2-digit Addendum	5-digit Addendum	Enable Standardization	Enable Expansion
UPC A	12	- 1	- 1	+ 2	+ 5	+ 1	0
UPC E	8	- 1	- 1	+ 2	+ 5	+ 1	+ 4
EAN 13	13	- 1	NC	+ 2	+ 5	NC	0
EAN 8	8	- 1	NC	+ 2	+ 5	NC	+ 5






Program

ALL

Family Code	PP	Parameter Selection	Option Code
 EAN 13 Check Digit Transmit	SS SS	Disable Enable ◀	6 7
 EAN 8 Check Digit Transmit	SS SS	Disable Enable ◀	8 9
 EAN ISBN/ISSN Convert	SS SS	Disable ◀ Enable	A B

- **EAN ISBN/ISSN Convert:** When enabled, the scanner converts and transmits EAN codes to ISBN or ISSN formats according to their prefixes respectively.

WPC Selection (UPC/EAN/CAN)	Basic Length	Disable Check Digit	Disable Numeric System	2-digit Addendum	5-digit Addendum	Enable Standardization	Enable Expansion
UPC A	12	- 1	- 1	+ 2	+ 5	+ 1	0
UPC E	8	- 1	- 1	+ 2	+ 5	+ 1	+ 4
EAN 13	13	- 1	NC	+ 2	+ 5	NC	0
EAN 8	8	- 1	NC	+ 2	+ 5	NC	+ 5






Program

ALL

Family Code	PP	Parameter Selection		Option Code	
 EAN 13 Security Level	SS	Level 0		0	
	SS	Level 1 ◀		1	
	SS	Level 2		2	
 EAN Supplement Scan Voting	SS	None	Level 7	0	7
	SS	Level 1	Level 8	1	8
	SS	Level 2	Level 9	2	9
	SS	Level 3 ◀	Level 10	3	A
	SS	Level 4	Level 11	4	B
	SS	Level 5	Level 12	5	C
	SS	Level 6	Level 13	6	D

- **EAN 13 Security Level** configures how the scanner decodes poorly-printed or out-of-spec EAN 13 barcodes. Level 2 has the highest level of sensitivity among the available levels. At Level 2, the scanner decodes barcodes quickly, but easily misreads barcodes, especially character numbers 1, 2, 7, and 8.
- **EAN 13 Security Level** is only available on 1D scanners.
- **EAN Supplement Scan Voting** determines how many times an UPC/EAN with 2/5-digit supplement has to be decoded before being transmitted. Supplement Scan Voting is only valid for UPC/EAN with 2-digit, 5-digit, or 2/5-digit supplements. Selecting a higher level might slow down the scanner when it reads poorly-printed, low contrast, or damaged barcodes.






Program

ALL

Family Code	PP	Parameter Selection	Option Code
 EAN Supplement Digits Select	SS	Ignore supplement digits ◀	0
	SS	EAN with 2-digit supplement	1
	SS	EAN with 5-digit supplement	2
	SS	EAN with 2- or 5-digit supplement	3
 EAN Supplement Digits Output	SS	Disable ◀	4
	SS	Enable	5
 EAN Addenda Separator	SS	Disable ◀	6
	SS	Enable	7

- **EAN Supplement Digits Select** configures which type of EAN code the scanner decodes according to its supplement digit format.
- **EAN Supplement Digits Output:** When enabled, the scanner transmits the EAN type that **EAN Supplement Digits Select** specifies together with its supplement digits.
- **EAN Addenda Separator:** With **EAN Supplement Digits Output** enabled and matching supplement digit format, enable this function to insert a space between the main EAN code and its supplement digits upon data transmission.



EAN - Prefix




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 <p>EAN Supplement Prefix</p>	SS	Ignore supplement digits ◀	0
	SS	Transmit supplemented EAN with all prefix types	1
	SS	Transmit supplemented EAN with prefix 491	2
	SS	Transmit supplemented EAN with prefix 978/979	3
	SS	Transmit supplemented EAN with prefix 977	4
	SS	Transmit supplemented EAN with prefix 378/379	5
	SS	Transmit supplemented EAN with prefix 414/419	6
	SS	Transmit supplemented EAN with prefix 434/439	7

EAN Supplement Prefix: When enabled, the scanner transmits EAN with supplement digits according to the prefix of the EAN. This function is only available when **EAN Supplement Digits Select** is set at **EAN with 2-digit supplement**, **EAN with 5-digit supplement**, or **EAN with 2- or 5-digit supplement**:

- **Ignore supplement digits:** When selected, the scanner decodes and transmits EAN codes without regarding its prefix and supplement.
- **Transmit supplemented EAN with all prefix types:** When selected, the scanner decodes any EAN with the supplement without regarding its prefix.
- **Transmit supplemented EAN with prefix 491:** When selected, the scanner transmits EAN starting with the number “491” if it has supplement digits. The scanner **DOES NOT** transmit EAN without supplement digits.
- **Transmit supplemented EAN with prefix 978/979:** When selected, the scanner transmits EAN starting with the number “978” or “979” if it has supplement digits. The scanner **DOES** transmit EAN without supplement digits.
- **Transmit supplemented EAN with prefix 977:** When selected, the scanner transmits EAN starting with the number “977” if it has supplement digits. The scanner **DOES** transmit EAN without supplement digits.




EAN - Prefix (continued)



Program

ALL

- **Transmit supplemented EAN with prefix 378/379:** When selected, the scanner transmits EAN starting with the number “378” or “379”. The scanner **DOES** transmits EAN without any supplement digits.
- **Transmit supplemented EAN with prefix 414/419:** When selected, the scanner transmits EAN starting with the number “414” or “419”. The scanner **DOES** transmits EAN without any supplement digits.
- **Transmit supplemented EAN with prefix 434/439:** When selected, the scanner transmits EAN starting with the number “434” or “439”. The scanner **DOES** transmits EAN without any supplement digits.



UCC Coupon Extended Code




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 UCC Coupon Extended Code Readability	SS	Disable ◀	0
	SS	Enable	1

UCC Coupon Extended Code: After enabling UPC A, EAN and Code 128 readability, enable this function to set the scanner to only decode UPC A barcodes starting with the digit “5”, EAN 13 barcodes with the digit “99”, and GS1 128 Coupon Codes.




ALL



Program

Family Code	PP	Parameter Selection	Option Code
 IATA Readability	SS	Disable ◀	0
	SS	Enable	1
 IATA Checking Length	SS	15-digit fixed length checking	2
	SS	Variable length checking ◀	3






Program

ALL

Family Code	PP	Parameter Selection	Option Code
 IATA Check Digit Verify	SS	Disable ◀	4
	SS	Enable automatic check digit	5
	SS	Verify check digit on S/N only	6
	SS	Verify check digit on CPN only	7
	SS	Verify check digit on CPN, Airline, and S/N	8
 IATA Check Digit Transmit	SS	Disable ◀	9
	SS	Transmit check digit	A
 IATA Start/Stop Transmit	SS	Disable ◀	B
	SS	Transmit start/stop characters	C

IATA Start/Stop Transmit: When enabled, the scanner transmits STX and ETX characters together with the decoded data.




Interleaved 25 (ITF)



Program

ALL

Family Code	PP	Parameter Selection	Option Code
 Interleaved 25 Readability	SS SS	Disable Enable ◀	0 1
 I25 Primary Format	SS SS	Interleaved 25 ◀ German Postal Code	2 3
 I25 Check Digit Verify	SS SS SS	Disable ◀ Verify with USS check digit Verify with OPPC check digit	4 5 6
 I25 Check Digit Transmit	SS SS	Disable ◀ Transmit check digit	7 8



Code 25 Family




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 Industrial 25 Readability	SS SS	Disable ◀ Enable	0 1
 Matrix 25 Readability	SS SS	Disable ◀ Enable	2 3
 China Postal Code Readability	SS SS	Disable ◀ Enable	4 5
 Code 25 Check Digital Verify	SS SS	Disable ◀ Verify check digit	6 7
 Code 25 Check Digit Transmit	SS SS	Disable ◀ Transmit check digit	8 9

Enable only one type of Code 25 at the same time, or set either maximum or minimum barcode length. Enabling multiple Code 25 types or allowing a changing data length might increase the chance of reading errors.



Code 25 Family (continued)




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 Code 25 Minimum Length	SS MS	Default (04) ◀ 01-Maximum	FIN (2 digits)
 Code 25 Maximum Length	SS MS	Default (98) ◀ 98-Minimum	FIN (2 digits)

- The data length excludes start/stop characters, such as the barcode ID.
- After scanning the 2 digits, the selection ends automatically.



Code 11




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 Code 11 Readability	SS SS	Disable ◀ Enable	0 1
 Code 11 Check Digit Verify	SS SS SS	Disable ◀ Verify with 1 modulo-11 check digit Verify with 2 modulo-11 check digits	2 3 4
 Code 11 Check Digit Transmit	SS SS	Disable ◀ Transmit check digit	5 6
 Code 11 Minimum Length	SS MS	Default (04) ◀ 01-Maximum	FIN (2 digits)
 Code 11 Maximum Length	SS MS	Default (98) ◀ 98-Minimum	FIN (2 digits)

- The data length excludes start/stop characters, such as the barcode ID.
- After scanning the 2 digits, the selection ends automatically.






Program

ALL

Family Code	PP	Parameter Selection	Option Code
 MSI Readability	SS SS	Disable ◀ Enable	0 1
 MSI Check Digit Select	SS SS SS	Verify with MOD 10 check digit ◀ Verify with MOD 10-10 check digit Verify with MOD 11-10 check digit	2 3 4
 MSI Check Digit Transmit	SS SS	Disable ◀ Transmit check digit	5 6






Program

ALL

Family Code	PP	Parameter Selection	Option Code
 MSI Minimum Length	SS MS	Default (04) ◀ 01-Maximum	FIN (2 digits)
 MSI Maximum Length	SS MS	Default (98) ◀ 98-Minimum	FIN (2 digits)

- The data length excludes start/stop characters, such as the barcode ID.
- After scanning the 2 digits, the selection ends automatically.






Program

ALL

Family Code	PP	Parameter Selection	Option Code
 UK/Plessey Readability	SS Disable ◀ SS Enable		0 1
 UK/Plessey Primary Format	SS Standard format ◀ SS CLSI format		2 3
 UK/Plessey X to A-F Convert	SS Disable ◀ SS Convert X to A-F		4 5
 UK/Plessey Check Digit Transmit	SS Disable ◀ SS Transmit check digit		6 7






Program

ALL

Family Code	PP	Parameter Selection	Option Code
 UK/Plessey Check Minimum Length	SS MS	Default (04) ◀ 01-Maximum	FIN (2 digits)
 UK/Plessey Check Maximum Length	SS MS	Default (98) ◀ 98-Minimum	FIN (2 digits)

- The data length excludes start/stop characters, such as the barcode ID.
- After scanning the 2 digits, the selection ends automatically.




Telepen

ALL



Program

Family Code	PP	Parameter Selection	Option Code
 Telepen Readability	SS	Disable Telepen ◀	0
	SS	Enable Telepen	1
 Telepen Primary Format	SS	Telepen Numeric mode	2
	SS	Telepen Full ASCII mode ◀	3
 Telepen Check Digit Transmit	SS	Disable ◀	4
	SS	Transmit check digit	5






Program

ALL

Family Code	PP	Parameter Selection	Option Code
 Telepen Minimum Length	SS MS	Default (04) ◀ 01-Maximum	FIN (2 digits)
 Telepen Maximum Length	SS MS	Default (98) ◀ 98-Minimum	FIN (2 digits)

- The data length excludes start/stop characters, such as the barcode ID.
- After scanning the 2 digits, the selection ends automatically.






Program

ALL

Family Code	PP	Parameter Selection	Option Code
 PDF417 Readability	SS	Disable	0
	SS	Enable ◀	1
 MicroPDF417 Readability	SS	Disable ◀	2
	SS	Enable	3




QR Code/Micro QR Code

2D ONLY



Program

Family Code	PP	Parameter Selection	Option Code
 QR Code Readability	SS	Disable	0
	SS	Enable ◀	1
 Micro QR Readability	SS	Disable	2
	SS	Enable ◀	3



QR Code/Micro QR Code (continued)




Program

2D ONLY

Family Code	PP	Parameter Selection	Option Code
 QR Code Append	SS SS	Disable Enable ◀	4 5
 QR Code Inverse Reading	SS SS SS	Disable Enable Auto detect ◀	6 7 8
 QR Code Mirror Images	SS SS SS	Disable Enable Auto detect ◀	9 A B

- **QR Code Append:** When enabled, the scanner only decodes and transmits data once it collects all the QR/Micro QR codes split from a single data message by Structured Append mode.
- **QR Code Inverse Reading:**
 - **Disable:** When selected, the scanner only decodes QR/Micro QR codes printed in a dark color over a light background.
 - **Enable:** When selected, the scanner only decodes QR/Micro QR codes printed in a light color over a dark background.
 - **Auto detect:** When selected, the scanner decodes both normal and inversed QR/Micro QR codes.
- **QR Code Mirror Images:**
 - **Disable:** When selected, the scanner only decodes standard QR/Micro QR codes.
 - **Enable:** When selected, the scanner only decodes mirrored (flipped) QR/Micro QR codes.
 - **Auto detect:** When selected, the scanner decodes both standard and mirrored QR/Micro QR codes.



QR Code/Micro QR Code (continued)




Program

2D ONLY

Family Code	PP	Parameter Selection	Option Code
 QR Code Minimum Length	SS MS	Default (01) ◀ 01-Maximum	FIN (4 digits)
 QR Code Maximum Length	SS MS	Default (7089) ◀ 7089-Minimum	FIN (4 digits)

- The data length excludes start/stop characters, such as the barcode ID.
- Supports both QR Code and Micro QR Code.
- After scanning the 2 digits, the selection ends automatically.



Data Matrix


2D ONLY



Program

Family Code	PP	Parameter Selection	Option Code
 Data Matrix Readability	SS	Disable	0
	SS	Enable ◀	1
 Data Matrix Inverse Reading	SS	Disable	4
	SS	Enable	5
	SS	Auto detect ◀	6
 Data Matrix Mirror Images	SS	Disable	7
	SS	Enable	8
	SS	Auto detect ◀	9

- **Data Matrix Inverse Reading:**
 - **Disable:** When selected, the scanner only decodes Data Matrix codes printed in a dark color over a light background.
 - **Enable:** When selected, the scanner only decodes Data Matrix codes printed in a light color over a dark background.
 - **Auto detect:** When selected, the scanner decodes both normal and inversed Data Matrix codes.
- **Data Matrix Mirror Images:**
 - **Disable:** When selected, the scanner only decodes standard Data Matrix codes.
 - **Enable:** When selected, the scanner only decodes mirrored (flipped) Data Matrix codes.
 - **Auto detect:** When selected, the scanner decodes both standard and mirrored Data Matrix codes.



Data Matrix (continued)




Program

2D ONLY

Family Code	PP	Parameter Selection	Option Code
 Data Matrix Minimum Length	SS MS	Default (01) ◀ 01-Maximum	FIN (4 digits)
 Data Matrix Maximum Length	SS MS	Default (3116) ◀ 3116-Minimum	FIN (4 digits)
 Data Matrix Poor Quality Reading	SS SS	Disable ◀ Enable	0 1

- **Data Matrix Minimum Length and Data Matrix Maximum Length:**
 - The data length excludes start/stop characters, such as the barcode ID.
 - After scanning the 2 digits, the selection ends automatically.
- **Data Matrix Poor Quality Reading** configures how well the scanner decodes a high density or poor quality Data Matrix code. Set the level higher to improve readability. Be aware that when this function is enabled, the snappiness of the scanner will be compromised.



MaxiCode

2D ONLY




Program

Family Code	PP	Parameter Selection	Option Code
 MaxiCode Readability	SS SS	Disable ◀ Enable	0 1
 MaxiCode Minimum Length	SS MS	Default (01) ◀ 01-Maximum	FIN (3 digits)
 MaxiCode Maximum Length	SS MS	Default (150) ◀ 150-Minimum	FIN (3 digits)

For **MaxiCode Minimum Length** and **Maximum Length**:

- The data length excludes start/stop characters, such as the barcode ID.
- After scanning the 2 digits, the selection ends automatically.



Aztec Code


2D ONLY



Program

Family Code	PP	Parameter Selection	Option Code
 Aztec Code Readability	SS SS	Disable Enable ◀	0 1
 Aztec Append	SS SS	Disable Enable ◀	2 3
 Aztec Inverse Reading	SS SS SS	Disable Enable Auto detect ◀	4 5 6

- **Aztec Append:** When enabled, the scanner only decodes and transmits data once it collects all the Aztec codes split from a single data message by Structured Append mode.
- **Aztec Inverse Reading:**
 - **Disable:** When selected, the scanner only decodes Aztec codes printed in a dark color over a light background.
 - **Enable:** When selected, the scanner only decodes Aztec codes printed in a light color over a dark background.
 - **Auto detect:** When selected, the scanner decodes both normal and inversed Aztec codes.



Aztec Code (continued)


2D ONLY



Program

Family Code	PP	Parameter Selection	Option Code
 Aztec Minimum Length	SS MS	Default (01) ◀ 01-Maximum	FIN (4 digits)
 Aztec Maximum Length	SS MS	Default (3832) ◀ 3832-Minimum	FIN (4 digits)

- The data length excludes start/stop characters, such as the barcode ID.
- After scanning the 2 digits, the selection ends automatically.



Australia Post Code


2D ONLY



Program

Family Code	PP	Parameter Selection	Option Code
 Australian Post Readability	SS	Disable ◀	0
	SS	Enable	1
 Australian Post Encode	SS	Transmit with raw format ◀	2
	SS	Transmit with numeric encoding (N Table)	3
	SS	Transmit with alphanumeric encoding (C Table)	4
	SS	Auto-discriminate encoding (Combine C & N Table)	5

- **Australia Post Encode** configures which encoding table the scanner refers to when decoding Australia Post Codes.
- **Auto-discriminate encoding** increases chance of misread because the encoded data format does not specify the encoding table it is based on.




British Post Code

2D ONLY



Program

Family Code	PP	Parameter Selection	Option Code
 British Post Readability	SS	Disable ◀	0
	SS	Enable	1
 British Post Check Digit Transmit	SS	Disable ◀	2
	SS	Transmit check digit	3




Netherlands KIX/Posi LAPA Code



Program

2D ONLY

Family Code	PP	Parameter Selection	Option Code
 Netherlands KIX Code Readability	SS	Disable ◀	0
	SS	Enable	1
 Posi LAPA Code Readability	SS	Disable ◀	0
	SS	Enable	1



Japan Post/Korea Post Code


2D ONLY



Program

Family Code	PP	Parameter Selection	Option Code
 Japan Post Readability	SS	Disable ◀	0
	SS	Enable	1
 Korea Post Readability	SS	Disable ◀	0
	SS	Enable	1

Korea Post Readability: Code length is fixed at 6 characters.




2D ONLY



Program

Family Code	PP	Parameter Selection	Option Code
 US Planet Readability	SS	Disable ◀	0
	SS	Enable	1
 US Planet Check Digit Transmit	SS	Disable ◀	2
	SS	Transmit check digit	3




US POSTNET

2D ONLY



Program

Family Code	PP	Parameter Selection	Option Code
 US POSTNET Readability	SS	Disable ◀	0
	SS	Enable	1
 US POSTNET Check Digit Transmit	SS	Disable ◀	2
	SS	Transmit check digit	3



Intelligent Mail


2D ONLY



Program

Family Code	PP	Parameter Selection	Option Code
 Intelligent Mail Readability	SS	Disable ◀	0
	SS	Enable	1

Intelligent Mail Readability: When enabled, the scanner decodes Intelligent Mail (USPS4CB/One Code) and transmits data.



GS1 128


ALL



Program

Family Code	PP	Parameter Selection	Option Code
 GS1 128 Readability	SS SS	Disable Enable ◀	0 1
 GS1 128 Minimum Length	SS MS	Default (01) ◀ 01-Maximum	FIN (2 digits)
 GS1 128 Maximum Length	SS MS	Default (98) ◀ 98-Minimum	FIN (2 digits)

- For **GS1 128 Minimum Length** and **GS1 128 Maximum Length**, the data length excludes start/stop characters, such as the barcode ID.
- After scanning the 2 digits, the selection ends automatically.




GS1 DataBar



Program

ALL

Family Code	PP	Parameter Selection	Option Code
 GS1 DataBar	SS	Disable GS1 DataBar	0
	SS	Enable GS1 DataBar ◀	1
 GS1 DataBar Ltd.	SS	Disable GS1 DataBar Limited	2
	SS	Enable GS1 DataBar Limited ◀	3
 GS1 DataBar Exp.	SS	Disable GS1 DataBar Expanded	4
	SS	Enable GS1 DataBar Expanded ◀	5






Program

ALL

Family Code	PP	Parameter Selection	Option Code
 GS1 DataBar Expanded Minimum Length	SS MS	Default (04) ◀ 01-Maximum	FIN (2 digits)
 GS1 DataBar Expanded Maximum Length	SS MS	Default (74) ◀ 74-Minimum	FIN (2 digits)
 GS1 DataBar Limited Security Level	SS SS SS	Level 1 Level 2 Level 3 ◀	0 1 2

- **GS1 DataBar Expanded Minimum Length and Maximum Length:**
 - The data length excludes start/stop characters, such as the barcode ID.
 - After scanning the 2 digits, the selection ends automatically.
- **GS1 DataBar Limited Security Level:**
 - Configures how well the scanner decodes poorly-printed or out-of-spec barcodes.
 - Level 1 is the most aggressive one and has the highest chance of a misread.
 - Only available on 1D scanners.




GS1 Composite Code




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 GS1 Composite Code Readability	SS	Disable ◀	0
	SS	Enable	1
 GS1 Composite Code UPC Link	SS	Disable ◀	2
	SS	Enable	3

- GS1 Composite Code UPC Link:** When disabled, the scanner transmits UPC regardless of the existence of an additional MicroPDF code. When enabled, the scanner only transmits those UPC codes extended with a MicroPDF code.



OCR A and OCR B


2D ONLY



Program

Family Code	PP	Parameter Selection	Option Code
 OCR Readability	SS	Disable ◀	0
	SS	Enable	1
 OCR Inverse Reading	SS	Disable ◀	0
	SS	Enable	1
	SS	Auto Detect	2
 OCR Reading Orientation	SS	L-to-R (up right) ◀	0
	SS	R-to-L (upside down)	1
	SS	B-to-T	2
	SS	T-to-B	3
	SS	Auto Detect	4

- OCR-A and OCR-B are supported by 2D Premium and Elite Models only.




OCR A and OCR B (continued)



Program

2D ONLY

Family Code	PP	Parameter Selection	Option Code
 OCR Reading Redundancy	SS	None ◀	0
	SS	Level1	1
 OCR Predefined Template	MS	ICAO_TD3 ◀	00
	MS	ICAO_TD2	01
	MS	ICAO_TD1	02
	MS	ICAO_VISA_A	03
	MS	ICAO_VISA_B	04
	MS	ICAO_ALL	05
	MS	ISBN_13	06
	MS	ISBN_10	07
	MS	ISBN_ALL	08
	MS	TWN_PASSPORT	20
	MS	CHN_IDCARD	21
	MS	CHN_TPC2015	22
	MS	CUSTOM	F0



4 Operation Modes

This chapter provides a complete list of available operation modes for each product series. To fulfill the needs of different application scenarios, the scanners' default modes and available mode options vary from series to series.

4.1 Operation Mode Settings

This section provides the command barcode for configuring the operation mode of your scanner. You can find the functional details of each parameter selection under each type of scanner.

Operation Mode - Corded Imager




Program

CORDED HANDHELD

Family Code	PP	Parameter Selection	Option Code
 Operation Mode	SS	Trigger mode ◀	1
	SS	Presentation mode	2
	SS	Force mode	9
	SS	Multiple read mode	C

- **Trigger Mode:** When enabled, the imager provides a longer Depth of Field (DOF) and goes into standby state after each reading for power saving. Press the trigger to activate the scanning process.
- **Presentation Mode:** When enabled, the preset background lighting of the imager will automatically turn on for barcode detection. The scanning process will automatically activate upon detecting a moving object within its field of view.
- **Force Mode:** The imager always keeps its LED illumination on and scans automatically for continuous operations.
- **Multiple Read Mode:** When enabled, press and hold the trigger to scan multiple barcodes continuously. The imager will beep after each successful scan. Upon decode timeout or releasing the trigger, the imager will switch to the standby state.




Operation Mode - Cordless Imager



Program

CORDLESS HANDHELD

Family Code	PP	Parameter Selection	Option Code
 Operation Mode	SS	Trigger mode ◀	1
	SS	Presentation mode	2
	SS	Multiple Read mode	C
 Trigger Toggle	SS	Disable ◀	0
	SS	BT on-screen keyboard	3
	SS		
	SS		
 Trigger Number	SS	2 Quick Triggers ◀	0
	SS	3 Quick Triggers	1
	SS	4 Quick Triggers	2

- **Trigger Mode:** When enabled, the imager provides a longer Depth of Field (DOF) and goes into standby state after each reading for power saving. Press the trigger to activate the scanning process.
- **Presentation Mode:** When enabled, the preset background lighting of the imager will automatically turn on for barcode detection. The scanning process will automatically activate upon detecting a moving object within its field of view.
- **Multiple Read Mode:** When enabled, press and hold the trigger to scan multiple barcodes continuously. The imager will beep after each successful scan. Upon decode timeout or releasing the trigger, the imager will switch to the standby state.
- **Trigger Toggle:** When enabled, you can switch the data input between the scanner and the on-screen keyboard of connected Bluetooth devices. Please refer to the “BT On-screen Keyboard” setting to select either the iOS Approach or the General Approach.
- **Trigger Number:** The number of times the trigger key must be pressed to activate the Trigger Toggle function.

OPTION CODE


0


4


7


9


C


1


5


8


A


D


2


6


B


E


3


FIN


F


END


FACTORY DEFAULT


Operation Mode - On Counter Scanner

ON COUNTER



Family Code	PP	Parameter Selection	Option Code
<p>Operation Mode</p>	SS	Trigger mode	1
	SS	Presentation mode ◀	2
	SS	Force mode	9
	SS	Multiple read mode	C

- **Trigger Mode:** When enabled, the scanner provides a longer Depth of Field (DOF) and goes into idle state after each reading. Press the trigger to activate the scanning process.
- **Presentation Mode:** When enabled, the preset background lighting of the scanner will automatically turn on for barcode detection. The scanning process will automatically activate upon detecting a moving object within its field of view.
- **Force Mode:** The scanner always scans automatically for continuous operations.
- **Multiple Read Mode:** When enabled, press and hold the trigger to scan multiple barcodes continuously. The scanner will beep after each successful scan. Upon decode timeout or releasing the trigger, the scanner will switch to the standby state.
- **When S690 enabled the HS680 function, the operation mode is only using Trigger mode and Presentation mode.**



Operation Mode - Companion Scanner



Program

COMPANION

Family Code	PP	Parameter Selection	Option Code
<p>Operation Mode</p>	SS	Trigger mode ◀	1
	SS	Multiple Read mode	C
<p>Trigger Toggle</p>	SS	Disable ◀	0
	SS	BT on-screen keyboard	3
<p>Trigger Number</p>	SS	2 Quick Triggers ◀	0
	SS	3 Quick Triggers	1
	SS	4 Quick Triggers	2

- **Trigger Mode:** When enabled, press the trigger to scan the barcode. Once the trigger is pressed, the scanner will execute a single scan. The scanning process will terminate upon decode timeout or releasing the trigger. Press the trigger to activate the next scanning process.
- **Multiple Read Mode:** When enabled, press and hold the trigger to scan multiple barcodes continuously. The scanner will beep after each successful scan. Upon decode timeout or releasing the trigger, the scanner will switch to the standby state.
- **Trigger Toggle:** When enabled, you can switch the data input between the scanner and the on-screen keyboard of connected Bluetooth devices. Please refer to the “BT On-screen Keyboard” setting to select either the iOS Approach or the General Approach.
- **Trigger Number:** The number of times the trigger key must be pressed to activate the Trigger Toggle function.

OPTION CODE

0

4

7

9

C

1

5

8

A

D

2

6

B

E

3

FIN

F

END

FACTORY DEFAULT


Operation Mode - Fixed Mount Scanner

FIXED MOUNT



Family Code	PP	Parameter Selection	Option Code
<p>Operation Mode</p>	SS	Trigger mode ◀	1
	SS	Presentation mode	2
	SS	Force mode	9
	SS	Multiple read mode	C

- **Trigger Mode:** When enabled, the scanner goes into idle state after each reading. The scanner provides a longer Depth of Field (DOF) and sends **Trigger On** command to activate the scanning process.
- **Presentation Mode:** When enabled, the scanner provides a higher motion tolerance and its background lighting will be activated for barcode detection. The aimer, illumination and scanning process will activate upon detecting an object.
- **Force Mode:** The scanner always keeps its LED illumination on and scans automatically for continuous operations.
- **Multiple Read Mode:** When enabled, the scanner sends **Trigger On** and **Trigger Off** serial commands to activate and terminate a multiple read decode session. During each multiple read decode session, the scanner beeps after each good read.



Operation Mode - Scan Module


SCAN MODULE



Program

Family Code	PP	Parameter Selection	Option Code
 Operation Mode	SS	Presentation mode ◀	1

- Presentation Mode:** When enabled, the scan module provides a higher motion tolerance and its background lighting will be activated for barcode detection. The aimer, illumination and scanning process will activate upon detecting an object.



5 Operation Control

This chapter presents the parameters related to the operation of your scanner. You will find settings for functionalities, including general scanner settings, user feedback control such as buzzer and vibration, and special parameters for different scanners.

5.1 Scanner Operation

This section provides the command barcodes for configuring the delay, timeout, sensitivity, and output response of your scanner. You can find the functional details of specified parameter selections.

Reread Delay/Good Read Delay




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 Reread Delay	SS	Disable	0
	SS	Immediate	1
	SS	Extremely short ◀	2
	SS	Short	3
	SS	Medium	4
	SS	Long	5
	SS	Force verification ◀ (Default of High Stationary Scanners)	6
	 Good Read Delay	SS	None ◀
SS		200 ms	1
SS		500 ms	2
SS		1 sec	3
SS		1.5 sec	4
SS		2 sec	5
SS		3 sec	6

- **Reread Delay** prevents the scanner from decoding the same barcode twice in a pre-defined duration. Among the options, **Force verification** prevents decoding the same barcode twice before the trigger session ends. Reread Delay is only effective under hands-free modes.
- **Good Read Delay** configures the length of interval between each good read.



Reread Delay Verification




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 Reread Delay Verification	SS	Last output	0
	SS	Multiple outputs ◀	1

- **Reread Delay Verification** prevents the scanner from reread outputs.
Last output prevents the scanner from outputting the same barcode consecutively by checking only the most recent output.
- **Multiple outputs** prevents the scanner from outputting the same barcode by checking a set of previously stored outputs.



Reset Reread Delay


ON COUNTER



Program

Family Code	PP	Parameter Selection	Option Code
 Reset Reread Delay	SS	Disable	0
	SS	Enable ◀	1

- Reset Reread Delay is only available for High Stationary Scanner.
- When “Reread Delay” is set to “Force Verification”, the same barcode(s) will not be output again in the next scan cycle. The “Reset Reread Delay” setting allows barcode(s) that were previously blocked due to the “Force Verification” setting to be reset, enabling them to be output again in subsequent scans.



Voice Feedback Delay


ON COUNTER



Program

Family Code	PP	Parameter Selection	Option Code
 Voice Feedback Delay	SS	500 ms ◀	0
	SS	1000 ms	1
	SS	1500 ms	2
	SS	2000 ms	3

- **Voice Feedback Delay** is only available for **High Stationary Scanner**.
- This is the delay time between the barcode being successfully decoded and the voice feedback.



Handheld Decode Timeout



Program

ALL

Family Code	PP	Parameter Selection	Option Code
 <p>Handheld Decode Timeout</p>	SS	Disable ◀	0
	SS	100 ms	1
	SS	200 ms	2
	SS	300 ms	3
	SS	400 ms	4
	SS	500 ms	5
	SS	600 ms	6
	SS	700 ms	7
	SS	800 ms	8
	SS	900 ms	9
	SS	1 sec	A
	SS	2 sec	B
	SS	4 sec	C
	SS	6 sec ◀ (Default of Cordless Bluetooth scanners)	D
	SS	8 sec	E
	MS	User-defined: 1 - 99 sec	F, (2 digits)

- Handheld Decode Timeout** configures the duration of a decode session under **Trigger mode** and **Multiple read mode**. When enabled, a decode session ends when any of following occurs:
 - The scanner successfully decodes and transmits a barcode during the decode session. The result is categorized as a “Good Read” (or an “OK”).
 - The scanner cannot decode any barcode before the time is up. The result is categorized as a “No Good Read” (or a “NG”).
 - Trigger or button of the scanner is released before the scanner can decode a barcode.
 - The scanner received a **Serial Trigger Off** command before it can decode a barcode.

OPTION CODE


0


4


7


9


C


1


5


8


A


D


2


6


B


E


3


FIN


F


END


FACTORY DEFAULT

Handheld Decode Timeout (continued)




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 <p>Handheld Decode Timeout</p>	SS	Disable ◀	0
	SS	100 ms	1
	SS	200 ms	2
	SS	300 ms	3
	SS	400 ms	4
	SS	500 ms	5
	SS	600 ms	6
	SS	700 ms	7
	SS	800 ms	8
	SS	900 ms	9
	SS	1 sec	A
	SS	2 sec	B
	SS	4 sec	C
	SS	6 sec ◀ (Default of Cordless Bluetooth scanners)	D
	SS	8 sec	E
	MS	User-defined: 1 - 99 sec	F, (2 digits)

- When **disabled**, a decode session ends when any of the above occurs except event ii: cannot decode any barcode before the time is up.



Hands-free Decode Timeout




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 <p>Hands-free Decode Timeout</p>	SS	100 ms	1
	SS	200 ms	2
	SS	300 ms	3
	SS	400 ms	4
	SS	500 ms	5
	SS	600 ms	6
	SS	700 ms	7
	SS	800 ms	8
	SS	900 ms	9
	SS	1 sec ◀ (Default of High Stationary scanners)	A
	SS	2 sec ◀ (Default of On-counter scanners)	B
	SS	4 sec	C
	SS	6 sec ◀	D
	SS	8 sec	E
	MS	User-defined: 1 - 99 sec	F, (2 digits)

- Hands-free Decode Timeout** configures the duration of a decode session under **Presentation mode**. A decode session ends when any of following event happens:
 - The scanner successfully decodes and transmits a barcode during the decode session. The result is categorized as a “Good Read” (or an “OK”).
 - The scanner cannot decode any barcode before the time is up. The result is categorized as a “No Good Read” (or a “NG”).



Presentation Scanning Activation




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 Presentation Scanning Activation	SS	Image motion detect ◀	0
	SS	IR proximity sensing ◀	1
	SS	Image proximity sensing	2

- **Presentation Scanning Activation** configures which sensor the scanner relies on to trigger a decode session under Presentation mode.
- **Handheld scanners, fixed mount scanners, companion scanners and high stationary scanners,** the default setting is **Image motion detect**.
- **On-counter scanners and embedded scan modules,** the default setting is **IR proximity sensing**.
 - **Image motion detect:** The scanner uses its image sensor to continuously monitor the environment when the scanner is in standby condition. It is triggered to scan upon detection of any object in motion within its field of view. Utilize **2D Image Sensitivity** to adjust the scanner's sensitivity when operating in image motion detect mode.
 - **IR proximity sensing:** The scanner uses its IR sensor to continuously monitor the environment when the scanner is in standby condition. It is triggered to scan when the IR sensor detects something entering its field of view and approaching the scanner. Utilize **IR Sensitivity** to adjust the sensitivity of the IR sensor when operating in IR proximity sensing mode.
 - **Image proximity sensing:** The scanner uses its image sensor to continuously monitor the environment when the scanner is in standby condition. It is triggered to scan when its image sensor detects something entering its field of view and approaching the scanner. The image proximity sensing mode requires sufficient background lighting to function accurately. In this mode, the background LED of the scanner is activated, regardless of the setting of the **2D Presentation Background Lighting** parameter.



Presentation Continuous Scan




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 Presentation Continuous Scan	SS	Continue after a good read	0
	SS	Discontinue after a good read ◀	1
	SS	Continue after a detection ◀	2

- High stationary scanners, the default setting is Continue after a detection.



Object-in/Object-out Message Output



Program

ON COUNTER

Family Code	PP	Parameter Selection	Option Code
 Object-in Message Output	SS	None ◀	0
	SS	Default message "OBJECT_IN" with CRLF	1
	MS	User-defined message	2, [00 - 7F]
 Object-out Message Output	SS	None ◀	0
	SS	Default message "OBJECT_OUT" with CRLF	1
	MS	User-defined message	2, [00 - 7F]

- **Object-in Message Output:** When enabled, the scanner sends out an "OBJECT_IN" message to the host when its image or IR-based proximity sensor detects any object entering its reading range and begins a decode session. Available under Presentation mode with either image or IR proximity sensing.
- **Object-out Message Output:** When enabled, the scanner sends out an "OBJECT_OUT" message to the host when its IR-based proximity sensor finds that the detected object leaving its reading range and ends the decode session. Only available under Presentation mode with IR proximity sensing.
- **Parameter Selection** allows 1 to 15 characters. Scan "FIN" to end the selection.

OPTION CODE


0


4


7


9


C


1


5


8


A


D


2


6


B


E


3


FIN


F


END


FACTORY DEFAULT

2D Image Sensitivity


2D ONLY



Program

Family Code	PP	Parameter Selection	Option Code
 2D Image Sensitivity	SS	Level 1	0
	SS	Level 2	1
	SS	Level 3	2
	SS	Level 4	3
	SS	Level 5 ◀	4
	SS	Level 6	5
	SS	Level 7	6

- 2D Image Sensitivity configures the sensitivity when the scanner uses its image sensor to trigger a decode session in Presentation mode; barcodes may not be detected due to insufficient ambient light. Choose higher levels of Presentation Sensitivity to improve barcode detection if needed. Setting the sensitivity level too high might cause unwanted triggering.



IR Sensitivity

ON COUNTER


SCAN MODULE



Program

Family Code	PP	Parameter Selection	Option Code
 IR Sensitivity	SS	Low ◀	0
	SS	High	1

- **IR Sensitivity** configures how sensitive the IR proximity sensor is.
- **Low:** The scanner exhibits lower sensitivity and is triggered to decode only when the target object enters the scanner’s field-of-view in close proximity and moves closer to the scanner.
- **High:** The scanner exhibits higher sensitivity and is triggered to decode when the target object enters the scanner’s field-of-view in considerable distance and gradually move closer to the scanner.



1D Barcode Inverse Reading




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 1D Barcode Inverse Reading	SS	Disable ◀	0
	SS	Enable	1

- **1D Barcode Inverse Reading:** When enabled, the scanner decodes 1D barcodes printed with a light color over a dark background.



Hands-free Timeout




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 Hands-free Timeout	SS	Short ◀	0
	SS	Medium	1
	SS	Long	2
	SS	Extremely long	3
	SS	Disable	4

- Under hands-free operation modes, the scanner automatically changes to Trigger mode when its trigger button is pressed. **Hands-free Timeout** controls the duration the scanner stays in Trigger mode. The timeout resets every time the trigger is pressed, and the scanner switches back to the original hands-free mode when the timeout is up.



Auto-sense Control


HANDHELD



Program

Family Code	PP	Parameter Selection	Option Code
 Auto-sense Control	SS	Disable ◀ (Default of Bluetooth scanners)	0
	SS	Enable ◀	1

- **Auto-sense Control:** When enabled, the scanner switches to hands-free mode automatically when a handheld corded scanner is placed on a Smart Stand, or when a handheld Bluetooth scanner is placed on a cradle.



Auto-sense Mode Select


HANDHELD



Program

Family Code	PP	Parameter Selection	Option Code
 Auto-sense Mode Select	SS	Presentation mode ◀	0
	SS	Force mode	2

- Auto-sense Mode Select configures which hands-free mode the scanner switches to when its Auto-sense function is enabled and triggered. Bluetooth scanners do not offer this particular function.



Laser Auto-sense Power Off Timeout




Program

LASER ONLY

Family Code	PP	Parameter Selection	Option Code
 Power Off Timeout	SS	3 min ◀	0
	SS	5 min	1
	SS	10 min	2

- Laser Auto-sense Power-off Timeout** configures how long the LED illumination of L-series Laser corded scanner stays on when its Auto-sense function is triggered.



NG Message Output

FIXED MOUNT

ON COUNTER



Program

Family Code	PP	Parameter Selection	Option Code
 NG Message Output	SS	None ◀	0
	SS	Default message "NG" with CRLF	1
	MS	User-defined message (1~15 characters)	2, [00 - 7F]

- When enabled, the scanner transmits a NG message when it has a No Good Read (NG) result.
- **Parameter Selection** allows 1 to 15 characters. Scan "FIN" to end the selection.

For character input, refer to the **HEX to ASCII Conversion Table** below:

L \ H	0	1	2	3	4	5	6	7
0	NUL	DLE	SPACE	0	@	P	`	p
1	SOH	DC1	!	1	A	Q	a	q
2	STX	DC2	*	2	B	R	b	r
3	ETX	DC3	#	3	C	S	c	s
4	EOT	DC4	\$	4	D	T	d	t
5	ENQ	NAK	%	5	E	U	e	u
6	ACK	SYN	&	6	F	V	f	v
7	BEL	ETB	'	7	G	W	g	w
8	BS	CAN	(8	H	X	h	x
9	HT	EM)	9	I	Y	i	y
A	LF	SUB	*	:	J	Z	j	z
B	VT	ESC	+	;	K	[k	{
C	FF	FS	,	<	L	\	l	
D	CR	GS	-	=	M]	m	}
E	SO	RS	.	>	N	^	n	~
F	SI	US	/	?	O	_	o	DEL

OPTION CODE


0


4


7


9


C


1


5


8


A


D


2


6


B


E


3


FIN


F


END


FACTORY DEFAULT

Handheld/Hands-free Alignment




Program

2D ONLY

Family Code	PP	Parameter Selection	Option Code
 Handheld Center Alignment	SS	Disable ◀	0
	SS	Enable ◀ (Default of On-counter scanners)	1
 Hands-free Center Alignment	SS	Disable ◀	2
	SS	Enable	3

- **Handheld Center Alignment:** When enabled, the scanner only decodes barcode(s) very close to the aiming line/dot under handheld modes including **Trigger mode** and **Multiple read mode**.
- **Hands-free Center Alignment:** When enabled, the scanner only decodes barcode(s) very close to the aiming line/dot under hands-free modes including **Presentation mode** and **Force mode**.



Handheld/Hands-free Alignment (continued)



Program

2D ONLY

Family Code	PP	Parameter Selection	Option Code
 Top of Center Window	MS	User-defined: 0-100%	[0-100], FIN
 Bottom of Center Window	MS	User-defined: 0-100%	[0-100], FIN
 Left of Center Window	MS	User-defined: 0-100%	[0-100], FIN
 Right of Center Window	MS	User-defined: 0-100%	[0-100], FIN

OPTION CODE


0


4


7


9


C


1


5


A


D


2


6


8


B


E


3


FIN


F


END


FIN


FACTORY DEFAULT


Handheld/Hands-free Alignment (continued)



Program

2D ONLY

- The default decoding area is an area of 40% top, 60% bottom, 40% left and 60% right of the scanner's field of view.
- By enabling Handheld/Hands-free Center Alignment, the scanner only decodes barcode(s) very close to the decoding area. You can define this area by configuring a desired percentage (0-100) for the **Top of Center Window**, **Bottom of Center Window**, **Left of Center Window** and **Right of Center Window**.
- When defining the decoding area, please refer to the illustration below. By setting the value of Bottom greater than that of Top and the value of Right greater than that of Left, the barcode will always stay within your scanner's field of view.



OPTION CODE				

ROI



Program

2D ONLY

FIXED MOUNT

SCAN ENGINE

Family Code	PP	Parameter Selection	Option Code
 ROI	SS Disable ◀ SS Enable		0 1
 Top of ROI	MS	User-defined: 0-100%	[0-100], FIN
 Bottom of ROI	MS	User-defined: 0-100%	[0-100], FIN
 Left of ROI	MS	User-defined: 0-100%	[0-100], FIN
 Right of ROI	MS	User-defined: 0-100%	[0-100], FIN

OPTION CODE




ROI (continued)



Program

2D ONLY FIXED MOUNT SCAN ENGINE

- **ROI:** When enabled, the scanner only reads barcodes that intersect a predefined decoding area. You can define this area by configuring a desired percentage (0-100) for the **Top of ROI**, **Bottom of ROI**, **Left of ROI** and **Right of ROI**.
- When defining the decoding area, please refer to the illustration below. By setting the value of Bottom greater than that of Top and the value of Right greater than that of Left, the barcode will always stay within your scanner's field of view.



OPTION CODE					

Unique Barcode Reporting


2D ONLY



Program

Family Code	PP	Parameter Selection	Option Code
 Unique Barcode Reporting	SS	Disable ◀	0
	SS	Enable	1

- Unique Barcode Reporting:** When enabled, the scanner only transmits each unique barcode one time before the trigger is released in Multiple read mode. Unique Barcode Reporting can prevent unwanted repeated reading of the same barcode.



2D Smart Scene


2D ONLY



Program

Family Code	PP	Parameter Selection	Option Code
 2D Smart Scene	SS	Auto mode ◀	0
	SS	Handheld optimized mode	1
	SS	Hands-free optimized mode	2
	SS	High motion mode	3
	SS	High density mode ◀(Default of High Stationary Scanner)	4
	SS	Smartphone mode	5

- 2D Smart Scene provides a series of pre-defined scanner profiles optimized for different application scenarios:
 - **Auto mode:** When selected, the scanner automatically switch to **Handheld optimized mode** in handheld Trigger mode and Multiple read mode, or switch to **Hands-free optimized mode** in hands-free Presentation mode and Force mode.
 - **Handheld optimized mode:** When selected, the scanner is configured for optimal reading range and can adapt to different lighting conditions effectively in all operation modes.
 - **Hands-free optimized mode:** When selected, the scanner is set up to deliver the best scanner response and improved motion tolerance across all operation modes.
 - **High motion mode:** When selected, the scanner is fine-tuned to read barcodes on rapidly moving objects at a consistent reading distance.
 - **High density mode:** When selected, the scanner is optimized to decode high density barcodes.
 - **Smartphone mode:** When selected, the scanner is configured to efficiently read barcodes displayed on self-illuminated surfaces with a glossy finish, like those found on smartphone or PC screens.



DPM Mode


2D ONLY



Program

Family Code	PP	Parameter Selection	Option Code
 DPM Mode	SS	Disable	0
	SS	DPM Standard Mode ◀	1

- **DPM Mode:** When enabled, the scanner uses an advanced DPM decoding algorithm to read challenging DPM codes.
- This function is only available for A800 series DP and all XD models.



Swift Serial Reading

FIXED MOUNT


2D ONLY



Program

Family Code	PP	Parameter Selection	Option Code
 Swift Serial Reading	SS	Disable ◀	0
	SS	Enable	1

- **Swift Serial Reading:** When enabled, the scanner outputs multiple adjacent 1D barcodes in sequence.



Batch Reading


ON COUNTER



Program

Family Code	PP	Parameter Selection	Option Code
<p>Batch Reading</p>	SS	Disable	0
	SS	Enable ◀	1

- **Batch Reading** is only available on **High Stationary Scanner**.
- **Batch Reading** enhances the scanner’s ability to decode barcodes located at the boundary of the scanning frame. This feature is particular useful when barcodes are misaligned or positioned away from the center, improving overall coverage and adaptability. Note that it may slightly increase decoding time due to the additional processing effort required.



Low Power State




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 Low Power State	SS	Disable ◀	0
	SS	Enable	1

- Low Power State:** When enabled, the scanner switches to the idle state after scanning activity, and then to the low power state after the preset low power timeout (see “Time Delay to Low Power State”) for power conservation. The scanner can be reactivated by pressing the trigger or when the host initiates communication with the scanner.



Time Delay to Low Power State




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 Time Delay to Low Power State	SS	1 sec	0
	SS	3 sec	1
	SS	5 sec	2
	SS	7 sec	3
	SS	9 sec	4
	SS	Immediate ◀	5

- Time Delay to Low Power State sets the time for scanner to switch to the low power state after any scanning activity.



Reading Redundancy




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 Reading Redundancy	SS	Level 1 ◀	1
	SS	Level 2	2
	SS	Level 3	3
	SS	Level 4	4
	SS	Level 5	5

- For all scanners, **Reading Redundancy** configures how many times a barcode has to be decoded and matches the previous result before it is transmitted. The level of reading redundancy is dynamically adjusted by the scanner based on the image quality and scanning conditions. The higher the level, the slower the scanning speed is with less chance of a misread. The lower the level, the faster the scanning speed is with higher chance of a misread.




1D Scan Rate

1D ONLY



Family Code	PP	Parameter Selection	Option Code
<p>1D Scan Rate</p>	SS	Dynamic ◀	0
	SS	Fixed	1

- 1D Scan Rate configures the exposure duration of each scan of a 1D scanner. When Fixed is selected, the motion tolerance is improved, while compromising the reading distance.



1D Reading Direction Indication




Program

1D ONLY

Family Code	PP	Parameter Selection	Option Code
 Direction Indication	SS	Disable ◀	0
	SS	Transmit direction character as prefix	1
	SS	Transmit direction character as suffix	2
	SS	Transmit direction character as prefix and suffix	3

- 1D Reading Direction Indication:** When enabled, the scanner attaches specified prefix and/or suffix characters to decoded data according to the reading direction of a 1D barcode, to identify whether the barcode is in its normal or reversed position.



Forward/Backward-read Indication



Program


1D ONLY

Family Code	PP	Parameter Selection	Option Code
 Forward-read Indication	SS	None ◀	0
	SS	“S”	1
	MS	User-defined character (1 character)	2 [00-7F]
 Backward-read Indication	SS	None	0
	SS	“X” ◀	1
	MS	User-defined character (1 character)	2 [00-7F]

- 1D Barcode Forward/Backward-reading Indication defines the characters attached and transmitted with the main data to identify the barcode direction.

For character input, refer to the HEX to ASCII Conversion Table below:

L \ H	0	1	2	3	4	5	6	7
0	NUL	DLE	SPACE	0	@	P	`	p
1	SOH	DC1	!	1	A	Q	a	q
2	STX	DC2	*	2	B	R	b	r
3	ETX	DC3	#	3	C	S	c	s
4	EOT	DC4	\$	4	D	T	d	t
5	ENQ	NAK	%	5	E	U	e	u
6	ACK	SYN	&	6	F	V	f	v
7	BEL	ETB	'	7	G	W	g	w
8	BS	CAN	(8	H	X	h	x
9	HT	EM)	9	I	Y	i	y
A	LF	SUB	*	:	J	Z	j	z
B	VT	ESC	+	;	K	[k	{
C	FF	FS	.	<	L	\	l	
D	CR	GS	-	=	M]	m	}
E	SO	RS	.	>	N	^	n	~
F	SI	US	/	?	O	_	o	DEL



OK/NG Signal Output


FIXED MOUNT



Program

Family Code	PP	Parameter Selection	Option Code
 Signal Output	SS	Disable OK output; disable NG output; disable OK/NG indicators ◀	0
	SS	Disable OK output; enable NG output ; disable OK/NG indicators	1
	SS	Enable OK output ; disable NG output; disable OK/NG indicators	2
	SS	Enable OK output ; enable NG output ; disable OK/NG indicators	3
	SS	Disable OK output; enable NG output ; enable NG indicator	4
	SS	Enable OK output ; disable NG output; enable OK indicator	5
	SS	Enable OK output ; enable NG output ; enable OK/NG indicators	6
	SS	Disable OK output; disable NG output; enable NG indicator	7
	SS	Disable OK output; disable NG output; enable OK indicator	8
	SS	Disable OK output; disable NG output; enable OK/NG indicators	9

- **OK/NG Signal Output:** When enabled, the scanner sends out an electrical signal through either the OK output pin or NG output pin according to the result of each decode session (Good Read or No Good Read). It is only effective in operation modes with the timeout function enabled.
- **OK/NG Indicators:** When enabled, the scanner emits a LED indicator according to the result of each decode session. It is only effective in operation modes with timeout function enabled.
- OK/NG signal outputs are only available on scanners with a FA400, FM400, FM500 series Universal Interface. These include FA490-9, FA480-9, FA470-9, FA460-9, FM590-9, FM580-9, FM490-9, FM480-9, SM5800-9, SM5600-9, and SM380-9.
- OK/NG indicators are available on all fixed mount scanner models.
- Only available on scanners with Universal interface.



OK/NG Signal Active State


FIXED MOUNT



Program

Family Code	PP	Parameter Selection	Option Code
 OK/NG Signal Active State	SS	Set OK low; set NG low ◀	0
	SS	Set OK low; set NG high	1
	SS	Set OK high; set NG low	2
	SS	Set OK high; set NG high	3

- **OK/NG Signal Active State** configures the logic level of the active state of OK/NG signal output. The scanner works as a NPN (sinking) device through OK and NG signal output pins.
- Scanners with a Universal Interface include FA480-9, FA470-9, FA460-9, FM480-9, SM5800-9, SM5600-9, and SM380-9.
- Only available on scanner with Universal Interface.



OK/NG Signal Duration


FIXED MOUNT



Program

Family Code	PP	Parameter Selection	Option Code	
 OK/NG Signal Duration	SS	10 ms	0	
	SS	20 ms	1	
	SS	30 ms	2	
	SS	40 ms	3	
	SS	50 ms	4	
	SS	60 ms	5	
	SS	70 ms	6	
	SS	80 ms	7	
	SS	90 ms	8	
	SS	100 ms ◀	9	
	MS	User-defined: 1 - 99 (x50) ms		A, (2 digits)

- OK/NG Signal Duration configures the duration of OK/NG signal outputs and OK/NG LED indications.



I/O Active State


SCAN ENGINE



Program

Family Code	PP	Parameter Selection	Option Code
 I/O Active State	SS	Active high	0
	SS	Active low ◀	1

- I/O Active State configures the active state of the Beeper and Good Read indicator pins of the scan engines or scan modules. For additional information, consult the integration manual specific to the scan engine or scan module product line.



User-defined Serial Trigger On/Off




Program

ALL

Family Code	PP	Parameter Selection	Option Code
<p>User-defined Serial Trigger On</p>	SS SS	None ◀ User-defined	0 1 [00-7F]
<p>User-defined Serial Trigger Off</p>	SS SS	None ◀ User-defined	0 1 [00-7F]

- **User-defined Serial Trigger On/Off** enables users to customize the serial command for triggering the scanner on or off.



Intelli Button Select




Program

2D ONLY FIXED MOUNT

Family Code	PP	Parameter Selection	Option Code
 Intelli Button Select	SS	iTunes ◀	0
	SS	Test Mode	1

- Intelli Button Select enables switching between iTunes and Test Mode, with iTunes as the default setting.



Barcode Position




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 Barcode Position	SS	None ◀	0
	SS	Center	1
	SS	Left-Top	2
	SS	4-Corners	3

- When **Barcode Position** is enabled, the barcode coordinates will be output following the raw data.
- There are delimiters between the raw data and the barcode position, as well as within the barcode position itself. You can configure the delimiter in the "Batch Field Delimiter" setting.



Companion Function Key Control




Program

COMPANION

Family Code	PP	Parameter Selection	Option Code
 Companion Function Key 1 Control	SS	Disable short and long press	0
	SS	Enable short press only	1
	SS	Enable long Press only	2
	SS	Enable short and long press ◀	3
 Companion Function Key 2 Control	SS	Disable short and long press	4
	SS	Enable short press only	5
	SS	Enable long Press only	6
	SS	Enable short and long press ◀	7

- Companion Function Key 1 & 2 Control configures the on or off of the short and long press on Function Key 1 (FN1) and Function Key 2 (FN2).



Command Barcode Lock

- Once the Command Barcode Lock is enabled, the scanner will no longer allow any settings to be changed by scanning barcode commands. Please contact cino technical support for further information.

5.2 Illumination Settings

This section provides the command barcodes for configuring the aimer and illumination settings of your scanner. You can find the functional details of specified parameter selections under each setting.

2D Illumination & Aiming Control


2D ONLY



Program

Family Code	PP	Parameter Selection	Option Code
<p>2D Handheld Illumination & Aiming Control</p>	SS	Disable illumination; disable aiming	0
	SS	Disable illumination; enable aiming	1
	SS	Enable illumination; disable aiming	2
	SS	Enable illumination; enable aiming ◀	3
<p>2D Hands-free Illumination & Aiming Control</p>	SS	Disable illumination; disable aiming	0
	SS	Disable illumination; enable aiming	1
	SS	Enable illumination; disable aiming ◀ (On-counter scanners)	2
	SS	Enable illumination; enable aiming ◀	3

- **2D Handheld Illumination & Aiming Control** configures the on/off of the illumination LED and aiming LED in trigger mode or multiple read mode.
- **2D Hands-free Illumination & Aiming Control** configures the on/off of the illumination LED and aiming LED in presentation mode or force mode.



2D Illumination Intensity


2D ONLY



Program

Family Code	PP	Parameter Selection	Option Code
 2D Handheld Illumination Intensity	SS	High ◀	0
	SS	Medium	1
	SS	Low	2
 2D Hands-free Illumination Intensity	SS	High ◀	0
	SS	Medium	1
	SS	Low	2

- **2D Handheld Illumination Intensity** configures the intensity of the illumination in trigger mode or multiple read mode.
- **2D Hands-free Illumination Intensity** configures the intensity of the illumination in presentation mode or force mode.



Auxiliary Illumination


FIXED MOUNT



Program

Family Code	PP	Parameter Selection	Option Code
 Auxiliary Illumination	SS	Disable ◀	0
	SS	Full light	1

- This function is only available for FA500 series.



2D Aiming Select/Pre-decode Aiming



Program

2D ONLY

Family Code	PP	Parameter Selection	Option Code
<p>2D Aiming Select</p>	SS	Regular Aiming ◀(Default of Bluetooth & 2D scan engines)	0
	SS	Intelligent Aiming ◀(Default of Corded & On-counter scanners)	1
	SS	Pre-decode Aiming	2
<p>2D Pre-decode Aiming Timeout</p>	SS	200 ms	0
	SS	400 ms ◀	1
	SS	800 ms	2
	SS	1 sec	3
	SS	1.5 sec	4
	SS	2 sec	5
	SS	3 sec	6
	SS	4 sec	7

- **2D Aiming Select** configures the 2D scanner behavior of aiming the line/dot with the 3 following options:
 - **Regular Aiming:** Aiming line/dot is turned on only when the trigger is pressed.
 - **Intelligent Aiming:** Aiming line/dot is turned on when the user lifts up the scanner, or when the scanner detects any movement in front of it.
 - **Pre-decode Aiming** provides a duration for the user to aim at the target barcode before the scanner turns on its LED illumination and starts to decode the barcode. The aiming line/dot stays on during **Pre-decode Aiming Timeout**. This mode is recommended when decoding many barcodes which are packed into a close distance. This option is only available under Trigger mode.
- **2D Aiming Select** is only available under Trigger mode and Multiple read mode.
- **2D Pre-decode Aiming Timeout** configures how long the duration is when the 2D scanner turns on its aiming line/dot before the decode session begins.

OPTION CODE

0

4

7

9

C

1

5

8

A

D

2

6

B

E

3

FIN

F

END

FIN

FACTORY DEFAULT

2D Presentation Background Lighting




Program

2D ONLY

Family Code	PP	Parameter Selection	Option Code
 2D Presentation Background Lighting	SS	Disable ◀	0
	SS	Enable ◀	1

- **2D Presentation Background Lighting** configures the behavior of the LED illumination in Presentation mode. When enabled, the scanner maintains a dim LED illumination in the background while on standby. Disabling the background lighting when the ambient light is poor could impede the scanner's responsiveness.
- The default setting of **On-counter scanners and scan modules** is **Disable**.
- In Presentation mode, if the scanner uses Image Proximity Sensing while its triggering method and background lighting are disabled, the scanner will not function properly.



Laser Aiming Control




Program

LASER ONLY

Family Code	PP	Parameter Selection	Option Code
 Laser Aiming Control	SS	Disable	0
	SS	Enable ◀	1

- Laser Aiming Control:** When disabled, the scanner turns off its Laser aiming line but keeps the LED illumination on when it is triggered. Disabling the Laser aiming line can improve the reading of stacked PDF417 and Micro PDF417 codes.



Laser Aiming Select, Pre-decode Aim




Program

LASER ONLY

Family Code	PP	Parameter Selection	Option Code
 Laser Aiming Select	SS	Regular aiming ◀	0
	SS	Pre-decode aiming	1
 Pre-decode Aim Timeout	SS	100 ms	0
	SS	150 ms ◀	1
	SS	200 ms	2
	SS	250 ms	3
	SS	300 ms	4

- Laser Aiming Select** configures the aiming line/dot behavior of L-series Laser scanners with 2 following options:
 - Regular aiming:** Aiming line/dot is turned on only when the trigger is pressed.
 - Pre-decode aiming** provides a duration for the user to aim at the target barcode before the scanner turns on its LED illumination and starts to decode the barcode. The aiming line/dot stays on during **Laser Pre-decode Aiming Timeout**. This mode is recommended when decoding many barcodes packed into a close distance. This option is only available under Trigger mode.
- Laser Aiming Select** is only available in Trigger mode and Multiple read mode.
- Laser Pre-decode Aiming Timeout** configures the length of time the laser scanner turns on its aiming line/dot before the decode session begins.



Illumination Color


2D ONLY



Program

Family Code	PP	Parameter Selection	Option Code
 Illumination Color	SS	White Illumination ◀	0
	SS	Red Illumination	1

- **Illumination Color** configures the color of your direct illumination with 2 following options:
 - **White Illumination:** The scanner turns on the white LED illumination.
 - **Red Illumination:** The scanner turns on the red LED illumination.
- This function is only available for A800 series.



DPM Illumination


2D ONLY



Program

Family Code	PP	Parameter Selection	Option Code
 DPM Illumination	SS	Direct Illumination	0
	SS	Diffused Illumination	1
	SS	Cycle Illumination ◀	2

- **Illumination Color** configures the source of your illumination.
 - **Direct Illumination:** The scanner turns on the direct illumination (dual-color lighting).
 - **Diffused Illumination:** The scanner turns on the diffused illumination (DPM diffuser).
 - **Cycle Illumination:** The scanner cycles between multiple light sources in a fixed sequence. To configure the length of interval between each light source, refer to **Illumination Rotation Interval**.
- This function is only available for A800 series DP models.



DPM Diffused Illumination


2D ONLY



Program

Family Code	PP	Parameter Selection	Option Code
 DPM Diffused Illumination	SS	Full Lighting ◀	0
	SS	Sided Lighting	1
	SS	Bottom Lighting	2

- **DPM Diffused Illumination** configures the behavior of your DPM diffuser.
 - **Full Lighting:** The scanner turns on the left, right and bottom sides of the DPM diffuser.
 - **Sided Lighting:** The scanner turns on the left and right sides of the DPM diffuser.
 - **Bottom Lighting:** The scanner turns on the bottom side of the DPM diffuser.
- This function is only available for A800 series DP models.



Illumination Rotation Interval


2D ONLY



Program

Family Code	PP	Parameter Selection	Option Code
 <p>Illumination Rotation Interval</p>	SS	500 ms	0
	SS	1 sec	1
	SS	1.5 sec	2
	SS	2 sec ◀	3
	SS	2.5 sec	4
	SS	3 sec	5
	MS	User-Defined 1-99 (x500) ms	6, (2 digits)

- **Illumination Rotation Interval** configures the length of interval between each light source for **Cycle Illumination**.
- This function is only available for A800 series DP models.



5.3 Audio & Indicator Settings

This section provides the command barcodes for configuring the audio and indicator settings of your scanner. You can find the functional details of specified parameter selections under each setting.

Buzzer Tone/Buzzer Volume



Program

ALL

Family Code	PP	Parameter Selection	Option Code
 Buzzer Tone	SS	Low (Frequency 1.20 kHz)	1
	SS	Medium (Frequency 2.70 kHz) ◀	2
	SS	High (Frequency 2.81 kHz)	3
	SS	Extremely high (Frequency 2.93 kHz)	4
 Buzzer Volume	SS	Low	0
	SS	Medium	1
	SS	High ◀	2

OPTION CODE


0


4


7


9


C


1


5


A


D


2


6


8


B


E


3


FIN


F


END


FACTORY DEFAULT


Good Read Beeping



Program

ALL

Family Code	PP	Parameter Selection	Option Code
 Good Read Beeping	SS	Disable	8
	SS	Enable ◀	7



Voice Feedback


ON COUNTER



Program

Family Code	PP	Parameter Selection	Option Code
 Voice Feedback	SS	Disable	0
	SS	Enable ◀	1

- **Voice Feedback** uses a human voice to indicate the number of barcodes scanned. This feature is only available on **High Stationary Scanners**.



Power On/Off Beeping



Program

ALL

Family Code	PP	Parameter Selection	Option Code
 Power On/Off Beeping	SS	Disable	6
	SS	Enable ◀	5

- **Power On/Off Beeping:** When enabled, the scanner emits a beeping sound right after it is powered on.
- Cordless Bluetooth scanners emit an additional beeping sound before being powered off.
- Power off beep is only available on cordless Bluetooth scanners.

OPTION CODE

 0	 4	 7	 9	 C
 1	 5	 8	 A	 D
 2	 6	 B	 E	 F
 3	<div style="border: 1px solid blue; padding: 5px; display: inline-block;">  FIN </div>			
 END			 FACTORY DEFAULT	

Good Read Indicator, Power Indicator



Program

ALL

Family Code	PP	Parameter Selection	Option Code
 Good Read Indicator	SS	Disable	0
	SS	Enable ◀	1
 Power Indicator	SS	Disable	0
	SS	Enable with LED steady on ◀	1
	SS	Enable with LED flashing	2

- **Power Indicator:** When enabled, the scanner illuminates its blue LED indicator to show that it is presently powered. A570, A560, F560, and all BT scanners do not support this function.

OPTION CODE


0


4


7


9


C


1


5


8


A


D


2


6


B


E


3


FIN


F


END


FACTORY DEFAULT

Vibration Control


HANDHELD



Program

Family Code	PP	Parameter Selection	Option Code
 Vibration Control	SS	Disable	0
	SS	Enable ◀	1

- **Vibration Control:** Only available on models with the vibration function.



Good Read Duration




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 Good Read Duration	SS	Short	0
	SS	Medium ◀	1
	SS	Long	2
	SS	Extreme long	3
	SS	Extreme short	4

- Good Read Duration is the duration of a good read beep.



OK/NG Beeping


FIXED MOUNT ON COUNTER



Program

Family Code	PP	Parameter Selection	Option Code
 OK/NG Beeping	SS	Disable OK beep; disable NG beep	0
	SS	Enable OK beep; enable NG beep	1
	SS	Enable OK beep; disable NG beep ◀	2
	SS	Disable OK beep; enable NG beep	3

- OK/NG Beeping:** When enabled, the scanner emits a corresponding buzzing beep corresponding to the result of each decode session (Good Read or No Good Read).



6 Bluetooth Settings

The information contained in this chapter pertains to the Bluetooth-related settings of FuzzyScan **cordless scanners**. The parameters presented herein are exclusively on Bluetooth models (such as batch scanning and validation scanning), as well as general Bluetooth settings related to device name, security, radio link and time-out.

6.1 General Bluetooth Settings

This section provides the command barcodes for configuring all Bluetooth-related settings on FuzzyScan cordless scanners. You can find the functional details of specified parameter selections under each setting.

BT Device Name



Program


BLUETOOTH

Family Code	PP	Parameter Selection	Option Code
 BT Device Name	SS MS	Default device name ◀ User-defined	FIN [00-7F], FIN

- Default BT Device Name differs according to product series:
 - **F / L / PF / PL series:** “FxxxBT-xxxx”, “LxxxBT-xxxx”, “PFxxxBT-xxxx” and “PLxxxBT-xxxx”; 1-16 characters
 - **A / PA series:** “AxxxBT-xxxx”, PAxxxBT-xxxx; 1-32 characters

For character input, refer to the HEX to ASCII Conversion Table below:

L \ H	0	1	2	3	4	5	6	7
0	NUL	DLE	SPACE	0	@	P	`	p
1	SOH	DC1	!	1	A	Q	a	q
2	STX	DC2	*	2	B	R	b	r
3	ETX	DC3	#	3	C	S	c	s
4	EOT	DC4	\$	4	D	T	d	t
5	ENQ	NAK	%	5	E	U	e	u
6	ACK	SYN	&	6	F	V	f	v
7	BEL	ETB	'	7	G	W	g	w
8	BS	CAN	(8	H	X	h	x
9	HT	EM)	9	I	Y	i	y
A	LF	SUB	*	:	J	Z	j	z
B	VT	ESC	+	;	K	[k	{
C	FF	FS	,	<	L	\	l	
D	CR	GS	-	=	M]	m	}
E	SO	RS	.	>	N	^	n	~
F	SI	US	/	?	O	_	o	DEL



BT PIN Code

BLUETOOTH




Program

Family Code	PP	Parameter Selection	Option Code
 BT PIN Code	SS MS	Default PIN code as “00000000” ◀ User-defined PIN code, 1 to 8 numbers	FIN [30-39], FIN

- Input PIN code by scanning HEX values (1-8 numbers), then scan FIN to finish the process.

For character input, refer to the HEX to ASCII Conversion Table below:

L \ H	0	1	2	3	4	5	6	7
0	NUL	DLE	SPACE	0	@	P	`	p
1	SOH	DC1	!	1	A	Q	a	q
2	STX	DC2	"	2	B	R	b	r
3	ETX	DC3	#	3	C	S	c	s
4	EOT	DC4	\$	4	D	T	d	t
5	ENQ	NAK	%	5	E	U	e	u
6	ACK	SYN	&	6	F	V	f	v
7	BEL	ETB	'	7	G	W	g	w
8	BS	CAN	(8	H	X	h	x
9	HT	EM)	9	I	Y	i	y
A	LF	SUB	*	:	J	Z	j	z
B	VT	ESC	+	;	K	[k	{
C	FF	FS	,	<	L	\	l	
D	CR	GS	-	=	M]	m	}
E	SO	RS	.	>	N	^	n	~
F	SI	US	/	?	O	_	o	DEL



BT Discoverable Protocol




Program

BLUETOOTH

Family Code	PP	Parameter Selection	Option Code
 BT Discoverable Protocol	SS	HID ◀	0
	SS	HID with Passkey	1
	SS	SPP Slave	3

- **BT Discoverable Protocol** configures which Bluetooth protocol the companion scanner uses when it is under discoverable mode. Press the FN1 button for 3 seconds to enter discoverable mode.
- **BT Discoverable Protocol** is only available for PA, PF, and PL series companion scanners.



BT Link Quality




Program

BLUETOOTH

Family Code	PP	Parameter Selection	Option Code
 BT Link Quality	SS	Disable ◀	0
	SS	Level 1	1
	SS	Level 2	2
	SS	Level 3	3
	SS	Level 4	4

- BT Link Quality:** When enabled, the reliability of the Bluetooth connection can be improved but with a shorter connection distance. This is recommended when operating the scanner near the boundary of the BT coverage zone. The higher the level, the more reliable the connection is within shorter distances. BT Link Quality is only available for Bluetooth SPP and Bluetooth HID protocols.



BT Out-of-range Scanning




Program

BLUETOOTH

Family Code	PP	Parameter Selection	Option Code
 BT Out-of-range Scan	SS	Disable ◀	0
	SS	Enable	1

- **BT Out-of-range Scanning:** When enabled, the scanner continues scanning when it loses radio link to the host device.



BT Radio Off Timeout




Program

BLUETOOTH

Family Code	PP	Parameter Selection	Option Code
<p>BT Radio off Timeout, Connected</p>	SS Disabled SS 60 minutes ◀ MS 1-99 (x5) minutes		0 FIN (2 digits)
<p>BT Radio off Timeout, Disconnected</p>	SS Disabled SS 1 minute ◀ MS 1-99 minutes		0 FIN (2 digits)

- **BT Radio off Timeout, Connected:** When enabled, the scanner automatically turns off its BT connection to save power if its trigger has not been pressed for the preset time duration. If the connection between the scanner and its host exists, the preset timeout is controlled by the “BT Radio off Timeout, Connected” parameter.
- **BT Radio off Timeout, Disconnected:** When enabled, the scanner automatically turns off its BT connection to save power if its trigger has not been pressed for the preset time duration. If the connection between the scanner and its host does not exist, the preset timeout is controlled by the “BT Radio off Timeout, Disconnected” parameter, which is significantly shorter than the timeout of a connected scanner.



BT Power off Timeout




Program

BLUETOOTH

Family Code	PP	Parameter Selection	Option Code
 BT Power off Timeout	SS	Immediately	0
	SS	5 minutes ◀	FIN
	MS	1-99 (x5) minutes	(2 digits)

- **BT Power off Timeout:** When enabled, the scanner automatically turns itself off when its radio link to the host device is not established before the preset timeout is due. Press the trigger to turn the scanner on again.



BT On-screen Keyboard



Program

BLUETOOTH

Family Code	PP	Parameter Selection	Option Code
 BT On-screen Keyboard	SS	iOS approach	0
	SS	General approach ◀	1

- **BT On-screen Keyboard** provides a way to toggle the primary keyboard of the host device between its own on-screen keyboard and a connected scanner. This function is supported by **most popular devices**. Select “**iOS Approach**” for iOS devices, or “**General Approach**” for most Android and other devices.
- After choosing the appropriate approach, use the “**Switch On-Screen Keyboard**” quick set command to switch the primary input method from the scanner to an on-screen keyboard. Scanning the “**Switch**”
- **On-Screen Keyboard** quick set command again will switch the input method back to scanner input.



Switch On-screen Keyboard

- For **PA, PF, and PL series** companion scanners, the **FN1 key** and **trigger key** can be used to switch the primary input method between scanner input and on-screen keyboard. For the **General Approach**, press the **FN1 key** shortly to switch the primary input method from the scanner to an on-screen keyboard. After you have finished typing on the **on-screen keyboard**, press the scanner’s trigger key once to turn off the on-screen keyboard and resume the BT connection.
- For the **iOS Approach**, press the **FN1 key** shortly to switch the primary input method between the scanner input and an on-screen keyboard.

OPTION CODE

 0	 4	 7	 9	 C
 1	 5	 8	 A	 D
 2	 6	 B	 E	 F
 3	<div style="border: 1px solid blue; padding: 5px; display: inline-block;">  FIN </div>	 END	 FACTORY DEFAULT	

BT HID Transmit Delay




Program

BLUETOOTH

Family Code	PP	Parameter Selection	Option Code
 BT Out-of-range Scan	SS MS	Disable ◀ 1-250 ms	FIN (3 digits)

- **BT HID Transmission Delay:**
 - When enabled, the transmission of BT HID is delayed for a more secured connection.
 - When the scanner is paired with an Android device, set the delay value to 70ms to avoid data loss.
 - After scanning the 3-digit code, the selection ends automatically.



BT Connect Beeping Control & Select




Program

BLUETOOTH

Family Code	PP	Parameter Selection	Option Code
 BT Connect Beep Control	SS	Enable ◀	0
	SS	Disable	1
 BT Connect Beep Select	SS	Four beeps ◀	0
	SS	Two beeps	1

- **BT Connect Beeping Control:** When enabled, the scanner emits a “connected” beep to indicate that the BT connection is established, or a “disconnected” beep to indicate that the connection is lost.
- **BT Connect Beeping Select** configures the style of the beeping:
 - **Four beeps:** When selected, the scanner emits four beeps in an ascending tone for a successful connection, and four beeps in a descending tone for a disconnection.
 - **Two beeps:** When selected, the scanner emits low to high toned beeps for a connection, and high to low toned beeps for a disconnection.



BT Battery Low Beeping




Program

BLUETOOTH

Family Code	PP	Parameter Selection	Option Code
 Battery Low Beeping	SS	Enable ◀	2
	SS	Disable	3

- **BT Battery Low Beeping:** When enabled, the scanner emits warning beeps if the battery power is lower than a certain level.



BT Low Power Link Indicator




Program

BLUETOOTH

Family Code	PP	Parameter Selection	Option Code
 BT Low Power Link Indicator	SS	LED indicator off	0
	SS	LED indicator lasts for 1 minute ◀	1
	SS	LED indicator stays on until the scanner powers off	2

- BT Low Power Link Indicator configures the behavior of the link status LED Indicator when the scanner goes into **Low Power Standby Mode** to save power.



BT Sniff Control




Program

BLUETOOTH

Family Code	PP	Parameter Selection	Option Code
 BT Sniff Control	SS	Disable ◀	0
	SS	Enable	1

- BT Sniff Control: When enabled, the Bluetooth scanner goes into Bluetooth Sniff Mode to lower power consumption.



BT Cradle PAIR Lock




Program

BLUETOOTH

Family Code	PP	Parameter Selection	Option Code
 BT Cradle PAIR Lock	SS	Locked PAIR mode	0
	SS	Unlocked PAIR mode ◀	1

- **BT Cradle PAIR Lock** configures the PAIR link between a scanner and the cradle it is pairing with.
 - **Locked PAIR mode:** When selected, the cradle is locked with the scanner it is paired with and rejects any pairing request from other scanners. Uninstall your scanner to free the cradle before pairing it with another scanner.
 - **Unlocked PAIR mode:** When selected, any pairing request from a scanner is accepted by the cradle. It also automatically cuts off the pairing with the previous scanner.



6.2 Bluetooth Special Modes

This section provides the command barcodes for configuring the batch and validation scanning operations. You can find the functional details of specified parameter selections under each setting.

Batch Scanning Link Control

BLUETOOTH



Program

Family Code	PP	Parameter Selection	Option Code
 Batch Scanning Link Control	SS	Disable	0
	SS	Enable ◀	1

- **Batch Scanning Mode (Inventory Mode)** is an exclusive function mode of FuzzyScan Bluetooth scanners. Under this mode the scanner stores decoded data in its memory and transmit the data as a data batch, instead of transmitting the data immediately after each decode. Scan following command barcodes to enter or exit the batch scanning mode:




Enter Batch Scanning



Exit Batch Scanning

- **Batch Scanning Link Control:** When disabled, the scanner cuts off its radio link to the host device once it enters batch scanning mode. The scanner resumes its radio link when transmitting data batches or exiting batch scanning mode.



Batch Scanning Data Transmit




Program


BLUETOOTH

Family Code	PP	Parameter Selection	Option Code
 Data Transmit	SS	On cradle or scan “Transmit Stored Data”	0
	SS	On cradle	1
	SS	Scan “Transmit Stored Data” ◀	2

- **Batch Scanning Data Transmit** configures when the scanner transmits its stored data to the host device under batch scanning mode.
- When **Scan “Transmit Stored Data”** is selected, scan the following barcode command to trigger data transmissions manually:



Transmit Stored Data



Batch Scanning Data Delete




Program


BLUETOOTH

Family Code	PP	Parameter Selection	Option Code
 Data Delete	SS	Disable ◀	0
	SS	Enable	1

- **Batch Scanning Data Delete:** When enabled, the scanner deletes all decoded data stored in its memory immediately after transmitting. When disabled, the scanner keeps all its decoded data until “Clear All Stored Data” is scanned.
- Scan the following barcode command to manually clean up all the stored data in the scanner’s memory:



Clear All Stored Data



Batch Scanning ID Output




Program

BLUETOOTH

Family Code	PP	Parameter Selection	Option Code
 ID Output	SS	Transmit scanned data only ◀	0
	SS	Transmit as <MAC address><Scanned data>	1
	SS	Transmit as <Scanner ID><Scanned data>	2

Batch Scanning ID Output:

- When enabled, the scanner adds extra info in front of the scanned data to identify the scanner.
- Only available with RS232 serial, USB HID, and USB CDC/Virtual COM interfaces under PAIR or PICO mode.



Batch Scanning Quantity Transmit



Program

BLUETOOTH

Family Code	PP	Parameter Selection	Option Code
 Batch Scanning Quantity Transmit	SS	Transmit as many times as the quantity indicates ◀	0
	SS	<Quantity><Field delimiter><Scanned Data>	1
	SS	<Scanned Data><Field delimiter><Quantity>	2

- **Batch Scanning Quantity Transmit** configures how quantity values are sent out to the host device in relation to the scanned data. To add a quantity value, scan the target barcode first then immediately enter a number between 1 and 9999 by scanning the corresponding **quantity option code(s)** as shown below. The entered quantity values are stored in memory and are later transmitted together with the barcode data in the selected format.
- **Transmit as many times as the quantity indicates:** When selected, the scanner transmits scanned data as many times as indicated by the entered quantity, instead of transmitting the quantity number directly.



Quantity Option 0



Quantity Option 5



Quantity Option 3



Quantity Option 8



Quantity Option 1



Quantity Option 6



Quantity Option 4



Quantity Option 9



Quantity Option 2



Quantity Option 7

OPTION CODE



0



4



7



9



C



1



5



8



A



D



2



6



B



E



3



FIN



F



END



FACTORY DEFAULT

Batch Field Delimiter



Program

BLUETOOTH

Family Code	PP	Parameter Selection	Option Code
 <p>Batch Field Delimiter</p>	SS	None	0
	SS	“ , ” (Comma) ◀	1
	SS	SPACE	2
	SS	“ - ”(Dash)	3
	SS	“ . ”(Period)	4
	SS	User-defined	5, [00-7F]

- **Batch Field Delimiter** configures the single character delimiter which separates scanned data and quantity value.

To enter the character, refer to the **HEX to ASCII Conversion Table** below:

L \ H	0	1	2	3	4	5	6	7
0	NUL	DLE	SPACE	0	@	P	`	p
1	SOH	DC1	!	1	A	Q	a	q
2	STX	DC2	"	2	B	R	b	r
3	ETX	DC3	#	3	C	S	c	s
4	EOT	DC4	\$	4	D	T	d	t
5	ENQ	NAK	%	5	E	U	e	u
6	ACK	SYN	&	6	F	V	f	v
7	BEL	ETB	'	7	G	W	g	w
8	BS	CAN	(8	H	X	h	x
9	HT	EM)	9	I	Y	i	y
A	LF	SUB	*	:	J	Z	j	z
B	VT	ESC	+	;	K	[k	{
C	FF	FS	,	<	L	\	l	
D	CR	GS	-	=	M]	m	}
E	SO	RS	.	>	N	^	n	~
F	SI	US	/	?	O	_	o	DEL

OPTION CODE


0


4


7


9


C


1


5


8


A


D


2


6


B


E


3


FIN


F


END


FACTORY DEFAULT

Validation Scanning Link Control



Program

BLUETOOTH

Family Code	PP	Parameter Selection	Option Code
 Validation Scanning Link Control	SS	Disable	0
	SS	Enable ◀	1

- Validation Scanning Mode is an exclusive function mode of FuzzyScan Bluetooth scanners. Under this mode the scanner can check whether or not the scanned barcode matches the registered master data. Scan following command barcodes to enter or exit the validation scanning mode:




Enter Validation Scanning



Exit Validation Scanning

- Validation Scanning Link Control:** When disabled, the scanner cuts off its radio link to the host device once it enters validation scanning mode. Radio link resumes later when the data transmission is activated or when the scanner exits validation scanning mode.



Validation Scanning Master Data



Program

BLUETOOTH

Family Code	PP	Parameter Selection	Option Code
 Validation Scanning Master Data	SS	Single master data ◀	0
	SS	Multiple master data	1

Validation Scanning Master Data configures if the validation scanning is based on a single master data or on multiple master data sets:

- **Single master data:** Scan the “Register Master Data” quick set command to start registering master data, and scan “Finish Registering” to end the registration. During the session the user can scan as many as barcodes, but only the last one can be stored and registered as the master data.
- **Multiple master data:** Scan the “Register Master Data” quick set command to start registering master data, and scan “Finish Registering” to end the registration. All barcodes scanned during the session are stored and registered as the master data. FuzzyScan Bluetooth scanners can store up to 2K bytes of master data. To clear all registered master data in the scanner’s memory, scan “Clear Master Data”.




Register Master Data



Finish Registering



Clear Master Data



Validation Scanning Output Select




Program

BLUETOOTH

Family Code	PP	Parameter Selection	Option Code
 Validation Scanning Output Select	SS	Disable data transmission ◀	0
	SS	Transmit valid data	1
	SS	Transmit invalid data	2
	SS	Transmit valid data or “NG”	3
	SS	Transmit invalid data or “OK”	4
	SS	Transmit “OK” or “NG”	5

- **Validation Scanning Output Select** configures how the scanner reacts after comparing the scanned data and the master data stored in its memory:
 - **Disable data transmission:** When selected, the scanner does not transmit anything. You can still recognize the comparison results by the “OK” or “NG” beep the scanner emits
 - **Transmit valid data:** When selected, the scanner only transmits matched result, and abandons mismatched data.
 - **Transmit invalid data:** When selected, the scanner abandons matched data, and only transmits mismatched data.
 - **Transmit valid data or “NG”:** When selected, the scanner transmits matched data or transmits a “NG” message if it is a mismatch.
 - **Transmit invalid data or “OK”:** When selected, the scanner transmits an “OK” message if it is a match or the mismatched data otherwise.
 - **Transmit “OK” or “NG”:** When selected, the scanner only transmits “OK” or “NG” message according to the match result, instead of transmitting the scanned data itself.



Companion FN2 Select




Program

BLUETOOTH

Family Code	PP	Parameter Selection	Option Code
 Companion FN2 Select	SS	Batch Scanning ◀	0
	SS	Validation Scanning	1

- Companion FN2 Select configures which BT special mode the scanner switches to when its Function Key No.2 (FN2) is pressed. This is only available on PA, PF, and PL series companion scanners.



7 Data Modification

This chapter presents the different parameters for altering data before the scanner transmits it. You will find the option to add extra characters or to include an informative element, as well as the parameters to control the powerful GS1 parsing tool.

7.1 Global Settings

This section provide the command barcodes for configuring the data to be transmitted. You can find the functional details of specified parameter selections under each command barcode.

Preamble

ALL



Program

Family Code	PP	Parameter Selection	Option Code
 Preamble	SS MS	None ◀ 1-15 characters	FIN [00-7F], [FIN]

- Parameter Selection allows 1-15 characters. Scan “FIN” to end the selection.
- STX and ETX are only transmitted under Serial Interfaces (RS232 and USB COM). The table below shows the complete **Message String**:

(STX)	Preamble	Scanned Data Length	Prefix Code ID	Scanned Data	Suffix Code ID	Postamble	(ETX)	Record Suffix (Serial)
(1 char.)	1-15 char.	2-4 digits	1 or 3 char.	Variable length	1 or 3 char.	1-15 char.	(1 char.)	1 char.

To enter the character(s), refer to the **HEX to ASCII Conversion Table** below:

L \ H	0	1	2	3	4	5	6	7
0	NUL	DLE	SPACE	0	@	P	`	p
1	SOH	DC1	!	1	A	Q	a	q
2	STX	DC2	*	2	B	R	b	r
3	ETX	DC3	#	3	C	S	c	s
4	EOT	DC4	\$	4	D	T	d	t
5	ENQ	NAK	%	5	E	U	e	u
6	ACK	SYN	&	6	F	V	f	v
7	BEL	ETB	'	7	G	W	g	w
8	BS	CAN	(8	H	X	h	x
9	HT	EM)	9	I	Y	i	y
A	LF	SUB	*	:	J	Z	j	z
B	VT	ESC	+	;	K	[k	{
C	FF	FS	,	<	L	\	l	
D	CR	GS	-	=	M]	m	}
E	SO	RS	.	>	N	^	n	~
F	SI	US	/	?	O	_	o	DEL

OPTION CODE


0


4


9


C


1


5


7


D


2


6


8


A


E


3


B


F


FIN


END


FACTORY DEFAULT

Postamble



Program

ALL


Family Code	PP	Parameter Selection	Option Code
 Postamble	SS MS	None ◀ 1-15 characters	FIN [00-7F], [FIN]

- Parameter Selection allows 1-15 characters. Scan “FIN” to end the selection.
- STX and ETX are only transmitted under Serial Interfaces (RS232 and USB COM). The table below shows the complete **Message String**:

(STX)	Preamble	Scanned Data Length	Prefix Code ID	Scanned Data	Suffix Code ID	Postamble	(ETX)	Record Suffix (Serial)
(1 char.)	1-15 char.	2-4 digits	1 or 3 char.	Variable length	1 or 3 char.	1-15 char.	(1 char.)	1 char.

To enter the character(s), refer to the **HEX to ASCII Conversion Table** below:

L \ H	0	1	2	3	4	5	6	7
0	NUL	DLE	SPACE	0	@	P	`	p
1	SOH	DC1	!	1	A	Q	a	q
2	STX	DC2	*	2	B	R	b	r
3	ETX	DC3	#	3	C	S	c	s
4	EOT	DC4	\$	4	D	T	d	t
5	ENQ	NAK	%	5	E	U	e	u
6	ACK	SYN	&	6	F	V	f	v
7	BEL	ETB	'	7	G	W	g	w
8	BS	CAN	(8	H	X	h	x
9	HT	EM)	9	I	Y	i	y
A	LF	SUB	*	:	J	Z	j	z
B	VT	ESC	+	;	K	[k	{
C	FF	FS	,	<	L	\	l	
D	CR	GS	-	=	M]	m	}
E	SO	RS	.	>	N	^	n	~
F	SI	US	/	?	O	_	o	DEL



Dollar Sign Convert




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 Dollar Sign Convert	SS	Output as “ \$ ” ◀	0
	SS	Output as “ ¥ ”	1
	SS	Output as “ € ”	2
	SS	Output as “ £ ”	3
	SS	Output as “ ¢ ”	4

- **Dollar Sign Convert** configures what the scanner actually transmits when it decodes a barcode containing the dollar sign.



FNC1 Transmit




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 FNC1 Transmit	SS	Disable	0
	SS	Enable ◀	1

- **FNC1 Transmit:** When enabled, the scanner transmits FNC1 (Function 1 Character) to the host if FNC1 is included in the decoded data.



Data Length Transmit



Program

ALL

Family Code	PP	Parameter Selection	Option Code
 Data Length Transmit	SS	Disable ◀	0
	SS	Enable	1


- **Data Length Transmit:** When enabled, the scanner transmits length information of the scanned data in a 2- or 4-digit format. If the data length is shorter than 100 characters, length information is sent as a 2-digit number.

The table below shows the complete **Keyboard Interface Message String (USB HID):**

Preamble	Scanned Data Length	Prefix Code ID	Scanned Data	Suffix Code ID	Postamble	Record Suffix (KB)
1-15 char.	2-4 digits	1 or 3 char.	Variable length	1 or 3 char.	1-15 char.	1 char.

The table below shows the complete **Serial Interface Message String (RS232, USB COM):**

STX	Preamble	Scanned Data Length	Prefix Code ID	Scanned Data	Suffix Code ID	Postamble	ETX	Record Suffix (Serial)
1 char.	1-15 char.	2-4 digits	1 or 3 char.	Variable length	1 or 3 char.	1-15 char.	1 char.	1 char.



Code ID Transmit



Program

ALL

Family Code	PP	Parameter Selection	Option Code
 <p>Code ID Transmit</p>	SS	Disable ◀	0
	SS	Transmit Cino ID as prefix	1
	SS	Transmit Cino ID as suffix	2
	SS	Transmit Cino ID as prefix and suffix	3
	SS	Transmit AIM ID as prefix	4
	SS	Transmit AIM ID as suffix	5
	SS	Transmit AIM ID as prefix and suffix	6


- Code ID Transmit:** When enabled, the scanner transmits code ID together with decoded data to identify the type of scanned barcode. Code ID can be transmitted either as a prefix, a suffix, or both. Refer to **Appendix - Code ID Table** for a complete list of Cino ID and AIM ID.

The table below shows the complete: **Keyboard Interface Message String (USB HID):**

Preamble	Scanned Data Length	Prefix Code ID	Scanned Data	Suffix Code ID	Postamble	Record Suffix (KB)
1-15 char.	2-4 digits	1 or 3 char.	Variable length	1 or 3 char.	1-15 char.	1 char.

The table below shows the complete **Serial Interface Message String (RS232, USB COM):**

STX	Preamble	Scanned Data Length	Prefix Code ID	Scanned Data	Suffix Code ID	Postamble	ETX	Record Suffix (Serial)
1 char.	1-15 char.	2-4 digits	1 or 3 char.	Variable length	1 or 3 char.	1-15 char.	1 char.	1 char.



ECI ID Transmit




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 ECI ID Transmit	SS	Disable ◀	0
	SS	Enable	1

- **ECI ID Transmit:** When enabled, the scanner transmits the ECI (Extended Channel Interpretation) ID embedded in the barcode.



7.2 GS1 Settings

This section provides the command barcodes for configuring GS1 data. You can find the functional details of specified parameter selections under each command barcode.

GS1 Special Function




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 GS1 Special Function	SS	Disable ◀	0
	SS	Enable	1

- GS1 Special Function:** When enabled, the scanner analyzes and transmits GS1 codes according to the settings of GS1-related parameters and GS1 formatter. When disabled, the scanner directly transmits these codes as normal barcodes. The **GS1 formatter** is provided by the FuzzyScan PowerTool 3 utility software.



GS1 1st FNC1 Transmit




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 GS1 1 st FNC1 Transmit	SS	Disable ◀	2
	SS	Enable	3

- GS1 1st FNC1 Transmit:** When enabled, the scanner converts the invisible FNC1 character in GS1 codes into a visible text string “]C1” and transmits it to the host. With this option, if there is more than one FNC1 character in the GS1 code, only the first FNC1 is converted.



GS1 Noninitial FNC1 Transmit



Program

ALL

Family Code	PP	Parameter Selection	Option Code
 GS1 Noninitial FNC1 Transmit	SS	None ◀	0
	SS	<GS> (1Dh)	1
	MS	User-defined character (1~2 characters)	2, [00-7F], [FIN]

- **GS1 Noninitial FNC1 Transmit:** In GS1 codes, non-initial FNC1 (FNC1 not located at the start of the barcode) is used to mark the end position of a data field with a variable length. When FNC1 Transmit is enabled and the GS1 contains a data field(s) with a variable data length, the scanner converts and transmits the invisible FNC1 character(s) accordingly.
 - **None:** The scanner divides the variable length data field according to the non-initial FNC1, but does not transmit the FNC1.
 - **<GS>:** The scanner converts the non-initial FNC1 to <GS> (value 1Dh) in serial interface, or its corresponding character in HID keyboard interface.
 - **User-defined:** The scanner converts the non-initial FNC1 to the user-defined value in a serial interface, or its corresponding character(s) in a HID keyboard interface.

To enter the character(s), refer to the HEX to ASCII Conversion Table below:

H \ L	0	1	2	3	4	5	6	7
0	NUL	DLE	SPACE	0	@	P	`	p
1	SOH	DC1	!	1	A	Q	a	q
2	STX	DC2	*	2	B	R	b	r
3	ETX	DC3	#	3	C	S	c	s
4	EOT	DC4	\$	4	D	T	d	t
5	ENQ	NAK	%	5	E	U	e	u
6	ACK	SYN	&	6	F	V	f	v
7	BEL	ETB	'	7	G	W	g	w
8	BS	CAN	(8	H	X	h	x
9	HT	EM)	9	I	Y	i	y
A	LF	SUB	*	:	J	Z	j	z
B	VT	ESC	+	;	K	[k	{
C	FF	FS	.	<	L	\	l	
D	CR	GS	-	=	M]	m	}
E	SO	RS	.	>	N	^	n	~
F	SI	US	/	?	O	_	o	DEL

OPTION CODE


0


4


7


9


C


1


5


A


D


2


6


8


B


E


3


FIN


F


END


FACTORY DEFAULT

GS1 AI Transmit




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 GS1 AI Transmit	SS	Do not transmit AI ◀	4
	SS	Transmit AI	5
	SS	Transmit AI enclosed with parentheses “(“ and “)”	6

- GS1 AI Transmit configures how the scanner processes the **Application Identifier (AI)** embedded in the GS1 code. When disabled, the scanner organizes decoded data before transmitting according to the embedded AIs, but does not directly transmit the AI characters themselves.



GS1 Failure Rule




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 GS1 Failure Rule	SS	Abandon data ◀	0
	SS	Transmit unparsed data	1

- **GS1 Failure Rule** configures how the scanner processes the decoded data when the GS1 parsing rule fails. GS1 Parsing fails under the following conditions:
 - The scanned data is labeled as GS1 but (part of) its format does not follow GS1 standard.
 - The scanned data contains rarely used Application Identifier (AI) not supported by FuzzyScan products.



GS1 Prefix/Suffix Output




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 GS1 Prefix/Suffix Output	SS	Output prefix/suffix of all AI fields ◀	0
	SS	Output prefix/suffix of existing AI fields only	1

- **GS1 Prefix/Suffix Output** configures how the scanner processes the user-defined prefix/suffix set by **GS1 formatter** in the PowerTool 3 utility software:
 - **Output prefix/suffix of all AI fields:** If you have set a prefix/suffix for a specific Application Identifier (AI) field but the AI doesn't exist in the GS1 code you scan, the scanner outputs the prefix/suffix without its corresponding AI and scanned data.
 - **Output prefix/suffix of existing AI fields only:** If you have set a prefix/suffix for a specific AI field but the AI doesn't exist in the GS1 code you scan, the scanner skips the AI and its corresponding prefix/suffix.



GS1 Format Mismatch Rule




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 GS1 Format Mismatch Rule	SS	Abandon data ◀	2
	SS	Output original data	3

- GS1 Format Mismatch Rule configures how the scanner processes the scanned GS1 data if all the Application Identifier (AI) fields in the barcodes mismatch with the AI fields you have defined with the GS1 formatter in PowerTool 3 utility software:
 - Abandon data: Abandon the complete GS1 code and transmit nothing.
 - Output original data: Keep the data and transmit it as a normal barcode without GS1 parsing.
- GS1 Format Mismatch Rule is only effective when GS1 Prefix/Suffix Output is set to “Output prefix/suffix of all AI fields”.



GS1 Date Field 'DD=00' Transmit




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 GS1 'DD=00' Transmit	SS	Disable	7
	SS	Transmit 'DD=00' ◀	8

- GS1 Date Field “DD=00” Transmit:** When enabled, the scanner transmits “00” directly if the data string contains date-type field and the last two digits of YYMMDD equals to “00”. When disabled, the scanner omits “00” and sends out YYMM instead.



GS1 Decimal Point Insert




Program

ALL

Family Code	PP	Parameter Selection	Option Code
 GS1 Decimal Point Insert	SS	Disable ◀	9
	SS	Enable	A

- **GS1 Decimal Point Insert:** When enabled, the scanner inserts a decimal point into each number-type data field if the decimal point position is implied in its Application Identifier (AI).



GS1 Element String Separator



Program


ALL

Family Code	PP	Parameter Selection	Option Code
 GS1 Element String Separator	SS	None ◀	FIN [00-7F], [FIN]
	MS	User-defined character (1-2 characters)	

- **GS1 Element String Separator:** When enabled, the user-defined character appears at the end of each element string except the last one.
- The FNC1 character is enclosed within the element string (positioned before the separator) if **GS1 Noninitial FNC1 Transmission Selection** is enabled.

To enter the character(s), refer to the **HEX to ASCII Conversion Table** below:

L \ H	0	1	2	3	4	5	6	7
0	NUL	DLE	SPACE	0	@	P	`	p
1	SOH	DC1	!	1	A	Q	a	q
2	STX	DC2	*	2	B	R	b	r
3	ETX	DC3	#	3	C	S	c	s
4	EOT	DC4	\$	4	D	T	d	t
5	ENQ	NAK	%	5	E	U	e	u
6	ACK	SYN	&	6	F	V	f	v
7	BEL	ETB	'	7	G	W	g	w
8	BS	CAN	(8	H	X	h	x
9	HT	EM)	9	I	Y	i	y
A	LF	SUB	*	:	J	Z	j	z
B	VT	ESC	+	;	K	[k	{
C	FF	FS	,	<	L	\	l	
D	CR	GS	-	=	M]	m	}
E	SO	RS	.	>	N	^	n	~
F	SI	US	/	?	O	_	o	DEL



GS1 Data Separator



Program


ALL

Family Code	PP	Parameter Selection	Option Code
 GS1 Data Separator	SS	None ◀	FIN [00-7F], [FIN]
	MS	User-defined character (1-2 characters)	

- **GS1 Data Separator:** When enabled, the user-defined character appears at the second dividing position between data sections within an element string if there are three or more data sections.
- For example, data field ITIP (AI 8006) has a format of N4+N14+N2+N2. If you set the comma (2Ch) as the GS1 Data Separator and enables AI transmission, the scanner actually transmits out (800) N14, N2, N2 for the specific element string.

To enter the character(s), refer to the **HEX to ASCII Conversion Table** below:

L \ H	0	1	2	3	4	5	6	7
0	NUL	DLE	SPACE	0	@	P	`	p
1	SOH	DC1	!	1	A	Q	a	q
2	STX	DC2	"	2	B	R	b	r
3	ETX	DC3	#	3	C	S	c	s
4	EOT	DC4	\$	4	D	T	d	t
5	ENQ	NAK	%	5	E	U	e	u
6	ACK	SYN	&	6	F	V	f	v
7	BEL	ETB	'	7	G	W	g	w
8	BS	CAN	(8	H	X	h	x
9	HT	EM)	9	I	Y	i	y
A	LF	SUB	*	:	J	Z	j	z
B	VT	ESC	+	;	K	[k	{
C	FF	FS	,	<	L	\	l	
D	CR	GS	-	=	M]	m	}
E	SO	RS	.	>	N	^	n	~
F	SI	US	/	?	O	_	o	DEL



8 Appendix

The Appendix contains additional information that is essential to the programming of your FuzzyScan barcode scanners. You will find useful tables pertaining to 1D barcode ID, 2D barcode ID, keyboard function codes, ASCII/HEX conversion, code pages.

8.1 Code ID Table - 1D Barcodes

Code ID Table - 1D Barcodes				
Code Family	Primary Format	Cino ID	AIM ID	
		Char.	Code Char.	Modified Char.
UPC	UPC A	A	E	0
	UPC A with 2 suppl.			1
	UPC A with 5 suppl.			2
	UPC E	E		0
	UPC E with 2 suppl.			1
	UPC E with 5 suppl.			2
AIM ID Example: UPC A barcode "012345678950" with 2-digit supplement "12" is sent as "JE0012345678950JE112"				
Code 128	Code 128	B	C	m
	GS1 128	C		1
Codabar	Codabar	D	F	m
Code 25	Industrial 25	I	S	0
	Matrix 25	K	X	0
	Interleaved 25	J	I	m
	China Postal Code	L	X	0
	German Postal Code	M	I	m
IATA	IATA	O	R	m
UCC Coupon	UCC Coupon Code	Z		
	AIM ID Examples: UPC A "512345678900" plus GS1 128 "81010123451297" is sent as "JE0512345678900JC181010123451297" EAN 13 "9923456789019" plus GS1 128 "81010123451297" is sent as "JE09923456789019JC181010123451297"			
EAN/JAN	EAN/JAN 8	N	E	4
	EAN/JAN 8 with 2 suppl.			1
	EAN/JAN 8 with 5 suppl.			2
	EAN/JAN 13	F		0
	EAN/JAN 13 with 2 suppl.			1
	EAN/JAN 13 with 5 suppl.			2
AIM ID Example: EAN/JAN-8 "49123562" with 5-digit supplement "12345" is sent as "JE449123562JE212345"				
Code 93	Code 93	H	G	m
Code 11	Code 11	P	H	m
MSI	MSI	R	M	m
UK/Plessey	UK/Plessey	S	P	0
Telepen	Telepen	T	B	m
GS1 DataBar	GS1 DataBar	X	e	m
	GS1 DataBar Limited			
	GS1 DataBar Expanded			
	GS1 Composite Code			
Code 39	Code 39	G	A	m
	Code 39 Trioptic	W	X	0
	Code 32	G	A	0
PDF417	PDF417	V	L	m
	Micro PDF417			
Korea Post	Korea Post Code	a	X	0
Each AIM Code Identifier contains a three-character string]cm where:] = Flag Character; c = Code Character; m = Modifier Character				

8.2 Code ID Table - 2D Barcodes

Code ID Table - 2D Barcodes				
Code Family	Primary Format	Cino ID	AIM ID	
		Char.	Code Char.	Modified Char.
QR Code	QR Code	b	Q	m
	Micro QR Code			
	GS1 QR Code	s		3
Data Matrix	Data Matrix	c	d	M
	GS1 Data Matrix	r		2
MaxiCode	MaxiCode	d	U	m
Aztec Code	Aztec Code	e	z	m
Australia Post	Australian Post	g	X	0
British Post	British Post	h		0
Intelligent Mail	Intelligent Mail	j		0
Japanese Post	Japanese Post	k		0
KIX Post	KIX Post	l		0
Posi LAPA Code	Posi LAPA Code	q		0
Planet Code	Planet Code	m		0
Postnet	Postnet	o		0

Each AIM Code Identifier contains a three-character string]cm where:
] = Flag Character; c = Code Character; m = Modifier Character

8.3 ASCII Input Shortcut

To configure user-definable parameters, scan the desired ASCII value in HEX form. See the “HEX/ASCII Table” for details.

Example:

To have data output lead with a Dollar Sign, set the “Preamble” to “\$”. The configuration procedure is listed below.

- Scan system command - **PROGRAM** to enter programming mode.
- Scan family code - **PREAMBLE**.
- See the Hex/ASCII Table. HEX value of “\$” is 24.
- Scan option code - 2.
- Scan option code - 4.
- Scan system command - **FIN (Finish)** to terminate Preamble setting.
- Scan system command - **End** to exit programming mode.

8.4 HEX/ASCII Reference Table

H \ L	0	1	2	3	4	5	6	7
0	NUL	DLE	SPACE	0	@	P	`	p
1	SOH	DC1	!	1	A	Q	a	q
2	STX	DC2	"	2	B	R	b	r
3	ETX	DC3	#	3	C	S	c	s
4	EOT	DC4	\$	4	D	T	d	t
5	ENQ	NAK	%	5	E	U	e	u
6	ACK	SYN	&	6	F	V	f	v
7	BEL	ETB	'	7	G	W	g	w
8	BS	CAN	(8	H	X	h	x
9	HT	EM)	9	I	Y	i	y
A	LF	SUB	*	:	J	Z	j	z
B	VT	ESC	+	;	K	[k	{
C	FF	FS	,	<	L	\	l	
D	CR	GS	-	=	M]	m	}
E	SO	RS	.	>	N	^	n	~
F	SI	US	/	?	O	_	o	DEL

Example: ASCII “A” →HEX “41”; ASCII “a” → “61”

■ : High Byte of HEX Value

□ : Low Byte of HEX Value

8.5 Function Key Output Table

	ASCII	ANSI	Function Key Character (Default)
00	00H	NUL	RESERVED
01	01H	SOH	CTRL (Left)
02	02H	STX	ALT (Left)
03	03H	ETX	SHIFT
04	04H	EOT	CAPS LOCK
05	05H	ENQ	NUM LOCK
06	06H	ACK	ESC
07	07H	BEL	F1
08	08H	BS	BACK SPACE
09	09H	HT	TAB
10	0AH	LF	F2
11	0BH	VT	F3
12	0CH	FF	F4
13	0DH	CR	ENTER (CR)
14	0EH	SO	F5
15	0FH	SI	F6
16	10H	DLE	F7
17	11H	DC1	F8
18	12H	DC2	F9
19	13H	DC3	F10
20	14H	DC4	F11
21	15H	NAK	F12
22	16H	SYN	INS (Insert) (Edit)
23	17H	ETB	DEL (Delete) (Edit)
24	18H	CAN	HOME (Edit)
25	19H	EM	END (Edit)
26	1AH	SUB	PAGE UP (Edit)
27	1BH	ESC	PAGE DOWN (Edit)
28	1CH	FS	UP (Edit)
29	1DH	GS	DOWN (Edit)
30	1EH	RS	LEFT (Edit)
31	1FH	US	RIGHT (Edit)

- To emulate the keystroke to send out special function characters under HID keyboard interface, you must configure actual content using the reserved ASCII 0 - 31 characters. You can change the output character of each key with User-defined Function Key, or by editing the Function Key Output Table via the PowerTool 3 software utility. Refer to Function Key Character Table for a complete list of special characters you can assign to each key.
- Function Key Emulation is applicable for IBM PP/XT/AT, PS/2, PS/VP, COMPAQ PP, HP Vectra PP, Notebook PP, APPLE and PowerMac, and WYSE PP Enhanced or fully compatible machines.

8.6 Function Key Character Table

	Category	Function Key Character	Option Code
1	Control Key	L-Ctrl + 2	01 1F
2	Control Key	L-Ctrl + a	01 04
3	Control Key	L-Ctrl + b	01 05
4	Control Key	L-Ctrl + c	01 06
5	Control Key	L-Ctrl + d	01 07
6	Control Key	L-Ctrl + e	01 08
7	Control Key	L-Ctrl + f	01 09
8	Control Key	L-Ctrl + g	01 0A
9	Control Key	L-Ctrl + h	01 0B
10	Control Key	L-Ctrl + i	01 0C
11	Control Key	L-Ctrl + j	01 0D
12	Control Key	L-Ctrl + k	01 0E
13	Control Key	L-Ctrl + l	01 0F
14	Control Key	L-Ctrl + m	01 10
15	Control Key	L-Ctrl + n	01 11
16	Control Key	L-Ctrl + o	01 12
17	Control Key	L-Ctrl + p	01 13
18	Control Key	L-Ctrl + q	01 14
19	Control Key	L-Ctrl + r	01 15
20	Control Key	L-Ctrl + s	01 16
21	Control Key	L-Ctrl + t	01 17
22	Control Key	L-Ctrl + u	01 18
23	Control Key	L-Ctrl + v	01 19
24	Control Key	L-Ctrl + w	01 1A
25	Control Key	L-Ctrl + x	01 1B
26	Control Key	L-Ctrl + y	01 1C
27	Control Key	L-Ctrl + z	01 1D
28	Control Key	L-Ctrl + [01 2F
29	Control Key	L-Ctrl + \	01 31
30	Control Key	L-Ctrl +]	01 30
31	Control Key	L-Ctrl + 6	01 23
32	Alt Key	L-Alt + a	04 04
33	Alt Key	L-Alt + b	04 05
34	Alt Key	L-Alt + c	04 06
35	Alt Key	L-Alt + d	04 07
36	Alt Key	L-Alt + e	04 08
37	Alt Key	L-Alt + f	04 09
38	Alt Key	L-Alt + g	04 0A
39	Alt Key	L-Alt + h	04 0B
40	Alt Key	L-Alt + i	04 0C

Function Key Character Table (continued)

	Category	Character	Option Code
41	Alt Key	L-Alt + j	04 0D
42	Alt Key	L-Alt + k	04 0E
43	Alt Key	L-Alt + l	04 0F
44	Alt Key	L-Alt + m	04 10
45	Alt Key	L-Alt + n	04 11
46	Alt Key	L-Alt + o	04 12
47	Alt Key	L-Alt + p	04 13
48	Alt Key	L-Alt + q	04 14
49	Alt Key	L-Alt + r	04 15
50	Alt Key	L-Alt + s	04 16
51	Alt Key	L-Alt + t	04 17
52	Alt Key	L-Alt + u	04 18
53	Alt Key	L-Alt + v	04 19
54	Alt Key	L-Alt + w	04 1A
55	Alt Key	L-Alt + x	04 1B
56	Alt Key	L-Alt + y	04 1C
57	Alt Key	L-Alt + z	04 1D
58	Alt Key	L-Alt + [04 2F
59	Alt Key	L-Alt + \	04 31
60	Alt Key	L-Alt +]	04 30
61	Alt Key	L-Alt + 6	04 23
62	Function Key	F1	00 3A
63	Function Key	F2	00 3B
64	Function Key	F3	00 3C
65	Function Key	F4	00 3D
66	Function Key	F5	00 3E
67	Function Key	F6	00 3F
68	Function Key	F7	00 40
69	Function Key	F8	00 41
70	Function Key	F9	00 42
71	Function Key	F10	00 43
72	Function Key	F11	00 44
73	Function Key	F12	00 45
74	Function Key	F13	00 68
75	Function Key	F14	00 69
76	Function Key	F15	00 6A
77	Function Key	F16	00 6B
78	Function Key	F17	00 6C
79	Function Key	F18	00 6D
80	Function Key	F19	00 6E

Function Key Character Table (continued)

	Category	Character	Option Code
81	Function Key	F20	00 6F
82	Function Key	F21	00 70
83	Function Key	F22	00 71
84	Function Key	F23	00 72
85	Function Key	F24	00 73
86	Keypad	Num Lock	00 53
87	Keypad	Keypad +	00 57
88	Keypad	Keypad -	00 56
89	Keypad	Keypad *	00 55
90	Keypad	Keypad /	00 54
91	Keypad	Keypad Delete	00 63
92	Keypad	Keypad 0 (Insert)	00 62
93	Keypad	Keypad 1 (End)	00 59
94	Keypad	Keypad 2 (Down)	00 5A
95	Keypad	Keypad 3 (Page Down)	00 5B
96	Keypad	Keypad 4 (Left)	00 5C
97	Keypad	Keypad 5	00 5D
98	Keypad	Keypad 6 (Right)	00 5E
99	Keypad	Keypad 7 (Home)	00 5F
100	Keypad	Keypad 8 (Up)	00 60
101	Keypad	Keypad 9 (Page Up)	00 61
102	Keypad	Keypad Enter	00 58
103	Modifier Key	L-Ctrl (Make)	11 EE
104	Modifier Key	L-Shift (Make)	22 EE
105	Modifier Key	L-Alt (Make)	44 EE
106	Modifier Key	L-Win (Make)	88 EE
107	Modifier Key	Alt GR (Make)	44 EF
108	Modifier Key	L-Ctrl (Break)	11 00
109	Modifier Key	L-Shift (Break)	22 00
110	Modifier Key	L-Alt (Break)	44 00
111	Modifier Key	L-Win (Break)	88 00
112	Navigation Key	Home	00 4A
113	Navigation Key	End	00 4D
114	Navigation Key	Page Up	00 4B
115	Navigation Key	Page Down	00 4E
116	Navigation Key	Up Arrow	00 52
117	Navigation Key	Down Arrow	00 51
118	Navigation Key	Left Arrow	00 50
119	Navigation Key	Right Arrow	00 4F
120	System & Edit Key	Tab	00 2B
121	System & Edit Key	ESC	00 29

Function Key Character Table (continued)

	Category	Character	Option Code
122	System & Edit Key	Print Screen	00 46
123	System & Edit Key	Pause/Break	00 48
124	System & Edit Key	Caps Lock	00 39
125	System & Edit Key	Scroll Lock	00 47
126	System & Edit Key	Insert	00 49
127	System & Edit Key	Delete	00 4C
128	System & Edit Key	Back Space	00 2A
129	System & Edit Key	Enter (CR)	00 28
130	System & Edit Key	Null	00 00
131	System & Edit Key	L-Ctrl	01 00
132	System & Edit Key	L-Shift	02 00
133	System & Edit Key	L-Alt	04 00
134	System & Edit Key	L-Win	08 00
135	System & Edit Key	Alt GR (R-Alt)	40 00

Examples of Usage:

- Set Enter on the Keypad as the Record Suffix under HID Keyboard interface:
 - Replace Enter (CR) with Enter Keypad by programming the scanner with the following command line:
[PROGRAM] [User-defined Function Key] [0D] [0058] [END]
 - In the command line, option code 1 [0D] is the hex value identifier of Enter (CR) in the default function key table, and option code 2 [0058] is the 4-digit code of Keypad Enter.
 - Set Enter Keypad as the user-defined character of Record Suffix (Keyboard) with the following command line:
[PROGRAM] [Record Suffix (Keyboard)] [5] [0D] [FIN] [END]
 - In the command line, option code 1 [5] is for selecting the user-defined character as the record suffix, and option code 2 [0D] is the identifier of Enter Keypad.
- Replace the noninitial FNC1 in GS1 barcodes with Ctrl characters under HID Keyboard interface:
 - Replace any two function keys with Ctrl characters with following two command lines:
[PROGRAM] [User-defined Function Key] [1E] [010A] [END]
[PROGRAM] [User-defined Function Key] [1F] [0116] [END]
 - In the first command line, option code 1 [1E] is the hex value identifier of the target function key slot, and option code 2 [010A] is the 4-digit code of **Ctrl + g**.
 - In the second command line, option code 1 [1F] is the hex value identifier of another target function key slot, and the option code 2 [0116] is the 4-digit code of **Ctrl + s**.
 - Replace noninitial FNC1 with user-defined Ctrl characters with following command line:
[PROGRAM] [Noninitial FNC1 Transmit] [2] [1E] [1F] [FIN] [END]
 - In the command line, option code 1 [2] is for selecting user-defined characters as the converted output for FNC1 characters, and option code 2 [1E] and [1F] are to set **Ctrl + g** and **Ctrl + s** as the user-defined characters.

8.7 Table of Corresponding Languages


Description	Code Page	Description	Code Page
Albanian	850	Hungarian	852
Arabic	1256	Icelandic	850
Arabic	720	Italian	850
Baltic	1257	Japanese	932
Bulgarian	866	Korean	949
Catalan	850	Latin 1	1252
Croatian	852	Latin 2	1250
Cyrillic	1251	Latin 5	1254
Czech	852	Latin American	850
Danish	850	Latvian	775
Dutch	850	Lithuanian	775
Estonian	775	Norwegian	850
English - United Kingdom	850	Polish	852
English - Australia	850	Portuguese	850
English - Canada	850	Romanian	852
English - New Zealand	850	Russian	866
English - United States	437	Serbian	855
English - South Africa	437	Slovakian	852
English - Philippines	437	Slovenian	852
Finnish	850	Spanish	850
French	850	Swedish	850
German	850	Chinese (Tradition)	950
Greece	737	Chinese (Simple)	936
Greece	1253	Thai	874
Hebrew - write	1255	Turkish	857
Hebrew Israel	862	Vietnamese	1258

8.8 Unicode Hex Input Setup


Windows - Setting up the Windows Registry

Step 1: Open the Registry Editor. You can do so by typing “regedit” in the “Search Windows” function or in Command Prompt.


Step 2: Go to HKEY_CURRENT_USER\Control Panel\Input Method.



Step 3: Right-click on your mouse or press shift + F10 (on keyboard) to add a new String Value (of type “REG_SZ”).



Step 4: Name the new String value as “EnableHexNumpad” and set its Value data to “1”.



Step 5: Reboot the computer.


Unicode Hex Input Setup (continued)

MAC - Adding Unicode Hex Input in menu bar

Step 1: Go to the Apple Menu -> System Preferences -> Keyboard




Step 2: On the Keyboard tab, click on “Input Sources” and check the “Show Input menu in menu bar” box.



Step 3: Click the “+” button to add an input source.

Step 4: Scroll to and select “Others”. Click on “Unicode Hex Input” (you can also use the Search function to find it). When done, click on the “Add” button.



Unicode Hex Input Setup (continued)

Step 5: Close the Keyboard Preferences menu.

Step 6: Change the input selection to Unicode Hex Input in the menu bar.



