




FUZZYSCAN SE480 Series OEM Scan Engine



A laser scan engine that delivers high performance and ease of integration

The SE480's exceptional capabilities and ultra-compact design are ideal for a wide range of OEM applications. Supported by the FuzzyScan imaging platform, it easily captures a variety of 1D and stacked barcodes, whether displayed on paper, plastic or digital screens. This imager engine also provides superior motion tolerance, as well as a reading speed of up to 500 scans per second. The SE480 offers full-sized performance in a small form factor that is easy to integrate.

- Sharp laser for quick and precise aiming
- Ultra-small and lightweight
- Easy to integrate
- Supports GS1 DataBar, PDF, MicroPDF and composite codes
- Superior readings on 3 mil barcodes, with a depth of field of over 3"
- Up to 34" reading range on regular barcodes
- Exceptional readings on low contrast, smudged, and damaged barcodes
- Superior motion tolerance for rapid captures of moving barcodes
- High speed scanning, up to 500 scans per second
- Supports various host interfaces: RS232, USB HID and USB COM
- Low power consumption

Scan All Your Needs

Quick and Precise Aiming

Aside from its LED illumination, the SE480 also projects a sharp laser beam to enhance aiming speed and accuracy in all environments. This laser beam can be especially useful when scanning barcodes of low height.

Capture Various Symbologies

This OEM scan engine is built to capture a vast array of 1D and stacked symbologies, whether displayed on paper, plastic or a digital screen. Stacked linear barcodes that can be read include PDF, MicroPDF, Codablock, GS1 DataBar stacked and composite codes.

Ready for Challenges

Barcode labels encountered in the real world are often in a less than ideal condition, which can make them difficult to scan. Empowered by Cino's FuzzyScan imaging platform, the SE480 is able to read various challenging and problematic barcodes, for example: low contrast, damaged, smudged, or poorly-printed barcodes.

Exceptional Reading Performance

In addition to an exceptional scan range on regular barcodes, the SE480 also delivers superior readings on high-density barcodes. Its performance and capabilities make it a versatile scan engine that is well-suited for diverse applications.

Miniature, Lightweight, Easy-to-Integrate

Ultra-compact and lightweight, the SE480 can be easily integrated into various portable or stationary devices, even those with space constraints, such as hand-held or fixed scanners, mobile computers, or PDAs.

SPECIFICATIONS

Performance Characteristics

Optical System	High-performance linear imaging engine
Print Contrast	20% minimum reflective difference
Minimum Resolution	Typical 3 mil (Code 39, PCS 0.9)
Reading Range *1	Up to 24 inches on 100% UPC/EAN symbols Up to 34 inches on 20 mil Code 39
Light Source	630nm visible red LED with laser aiming
Scan Rate	Dynamic scanning rate, up to 500 scans per second
Reading Direction	Bi-directional (forward and backward)
Scan Angle	42°
Pitch/Skew	± 65° / ± 55°
Operating Modes	Low power, Trigger, Force, Level, Alternative, Presentation
Host Interfaces	TTL RS-232 serial, USB HID (USB Keyboard), USB COM port emulation
Configuration Setup	Command barcodes, API serial command
Data Editing	DataWizard Premium

Physical Characteristics

Dimensions	23.0 mm (D) x 21.0 mm (W) x 11.9 mm (H) 0.91 in. (D) x 0.82 in. (W) x 0.47 in. (H)
Weight	6 g
Input Voltage	3.3VDC ± 10%
Current	Scanning : Typical 150 mA @3.3VDC Standby : 50 µA @3.3VDC (Low power mode)
Connector	12-pin low profile

1. The Reading Range are measured under Cino's test environmental condition.
2. Don't stare into the LED beam.

Supported Symbolologies

1D Linear Barcodes	Code 39, Code 39 Full ASCII, Code 32, Code 39 Trioptic, Code 128, GS1-128, Codabar, Code 11, Code 93, Standard & Industrial 2 of 5, Interleaved & Matrix 2 of 5, German Postal Code, China Postal Code, IATA, UPC/EAN/JAN, UPC/EAN/JAN with Addendum, Telepen, MSI/Plessey & UK/Plessey, GS1 DataBar (formerly RSS) Linear
Stacked Linear Barcodes	GS1 DataBar Stacked, PDF417, Micro PDF417, Codablock F, Composite

User Environment

Operating Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
Storage Temperature	-40 °C to 70 °C (-40 °F to 158 °F)
Humidity	5% to 95% related humidity, non-condensing
Ambient Light Immunity	0-100,000 lux

Safety & Regulatory

Safety*2	Laser Eye Safety IEC60825-1, Class 1 Led eye safety IEC62471, Exempt Group
Environmental	Compliant with RoHS directive

Evaluation Kit



Evaluation Board



Cable Set